

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

RECEIVED WATER WELL REPORT JUN 29 1967 STATE OF OREGON (Please type or print) STATE ENGINEER SALEM, OREGON

March 1968 G 5426

State Well No. 19/47-B E

State Permit No. #12947

db

(1) OWNER:

Name K. S. & D. FARMERS Address YTURKI & OKIEF ONTARIO ORE.

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven [x] Cable [x] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Irrigation [x] Test Well [] Other []

(5) CASING INSTALLED:

16" Diam. from 7'1" ft. to 46' ft. Gage 4" 13" Diam. from 70' ft. to 110' ft. Gage 4"

(6) PERFORATIONS:

Perforated? [x] Yes [] No. Type of perforator used TORCH Size of perforations 3/8" in. by 6" in. 3/16 x 6" 240 perforations from 27' ft. to 47' ft. 180 perforations from 70' ft. to 110' ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 24' ft. below land surface Date 6-3-67 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [x] Yes [] No If yes, by whom? DRILLER 586 gal./min. with 96 ft. drawdown after 12 hrs. Bailer test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m. Date Temperature of water 61° Was a chemical analysis made? [] Yes [x] No

(10) CONSTRUCTION:

Well seal—Material used CONCRETE Depth of seal 31 ft. Diameter of well bore to bottom of seal 24" in. Were any loose strata cemented off? [x] Yes [] No Depth 4 to 21' Was a drive shoe used? [x] Yes [] No Did any strata contain unusable water? [] Yes [x] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [x] Yes [] No Size of gravel: 3/4 x 3/8 Gravel placed from 31' ft. to 45' ft.

(11) LOCATION OF WELL:

County MALHEUR Driller's well number NW 1/4 SE 1/4 Section 8 T. 19S R. 47E W.M. Bearing and distance from section or subdivision corner 4023' North and 49°45' minutes EAST of SW CORNER Sec 8.

(12) WELL LOG:

Diameter of well below casing 16 1/2" Depth drilled 145' ft. Depth of completed well 145' ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include SOIL SANDY, SANDY SANDY, SANDY GRAVEL, CLAY BLUE, SAND BLACK, CLAY BLUE, SAND BLACK.

Work started 5-19 1967 Completed 6-3 1967 Date well drilling machine moved off of well 6-3 1967

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Sue J. Nailor Date 6-26, 1967 (Drilling Machine Operator)

Drilling Machine Operator's License No. 101

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME HOLLONAY DRILLING CO (Person, firm or corporation) (Type or print)

Address ONTARIO ORE

[Signed] Max Hollonay (Water Well Contractor)

Contractor's License No. 16 Date 6-26, 1967