WATER WELL REPORT STATE OF OREGON

RECEIVED State Well No.

JUL 28 1981

WATER RESOURCES DEPITATION No. SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:	
Name CARL SETTS	County MATHEUR Driller's well	number
Address RT 2 BOX 130		R. 47 W.M.
City NYSSA, OREGON 97913 State	Tax Lot # 1000 Lot Blk	Subdivision
2) TYPE OF WORK (check):	Address at well location:	
New Well X Deepening □ Reconditioning □ Abandon □ f abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	ell.
	Depth at which water was first found	22 _{ft.}
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Static level 8 ft. below la	nd surface. Date 7/20/8
Rotary Air M. Driven D Domestic Industrial Municipal Rotary Mud Dug Marie Trigation M. Test Well D Other	Artesian pressure lbs. per	r square inch. Date
Cable Bored Thermal: Withdrawal Reinjection	(12) WELL LOG: Diameter of well below c	easing 811
5) CASING INSTALLED: Steel X Plastic	Depth drilled 35 - ft. Depth of o	,, <u></u>
8 "Diam from ft. to ft. Gauge	Formation: Describe color, texture, grain size and structhickness and nature of each stratum and aquifer penetror each change of formation. Report each change in pand indicate principal water-bearing strata.	rated, with at least one entry
LINER INSTALLED:	MATERIAL	From To SWL
"Diam. from	Top Soil	0 1
(A) TOTAL ASSESSMENT OF THE SECOND OF THE SE	Soft Brown Clay	1 15
(6) PERFORATIONS: Perforated? W Yes I No Type of perforator used FACTORY	Fine Brown Sand	15 22
Size of perforations $\frac{1}{8}$ in. by $\frac{4}{1}$ in.	Small Gravel & Blue Sand	22 25 8
72 perforations from 27 ft. to 32 ft.	Medium Gravel & Coarse	
· ·	Gray & White Sand w/b	25 32 8
perforations from	Rlue Clay	32 35
perforations from ft. to ft.		
7) SCREENS: Well screen installed? Yes X No	· I	
Manufacturer's Name		
Type Model No.		
Diam. Slot Size Set from ft. to ft.		
Diam. Slot Size Set from ft. to ft. Drawdown is amount water level is lowered		
8) WELL TESTS: Drawdown is amount water level is towered below static level		
Was a pump test made:		
gal/min. with ft. drawdown after hrs.		
// // // // // // // // // // // // //		
Air test 60 gal./min. with drill stem at 25 ft. 1 hrs.		
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
erature of water 55 Depth artesian flow encounteredft.	Work started 7/20/81 19 Completed	a 7/20/81 19
9) CONSTRUCTION: Special standards: Yes \(\subseteq \) No \(\subseteq \)	Date well drilling machine moved off of well	7/20/81 19
Well seal—Material used CEMENT	Drilling Machine Operator's Certification:	
Well sealed from land surface to	This well was constructed under my direct su	pervision. Materials used
Diameter of well bore to bottom of sealin.	and information reported above are true to my be	est knowledge and belief.
Diameter of well bore below sealin.	[Signed] (Drilling Machine Operator)	Date7/22,19.81
Number of sacks of cement used in well seal	Drilling Machine Operator's License No	.05
How was cement grout placed?		
PRESSURII-GROUTED	Water Well Contractor's Certification:	7.77
Transport to the 11-10	This well was drilled under my jurisdiction the best of my knowledge and belief.	and this report is true to
Vas pump installed?	Name PAGE BROTHERS DRILLI	NG -
Was a drive shoe used?	(Person, firm or corporation)	(Type or print)
Type of Water? depth of strata	Address RT 2 BOX 371 VALE	, OREGON 979
Method of sealing strata off	[Signed] MANAGER	de
Was well gravel packed: 1 Yes 1 No Size of gravel:	(Water Well Contractor	
Gravel placed from	Contractor's Licepse No. 564 Date	7/22/,1981
A THE PARTY OF THE		