ORIGINAL File Original and Duplicate with the STATE ENGINEER SALEM, OREGON	DBSERVATION WELL State Well No. 20/46 - 28 G /I) OF OREGON (2/46 - 28 G /I)
	State Permit No. 453
(1) OWNER: Henrietta and Ge orge Mendazona	(11) WELL TESTS. Drawdown is amount water level is lowered below static level
Address R+ in	Was a pump test made? Wes No If yes, by whom? Mo
Nyssa, Oregon	Yield: 600 gal./min. with 40 ft. drawdown after 7 hrs.
(2) LOCATION OF WELL:	7
County A WELL:	Bailer test gal./min. with ft. drawdown after hrs.
NW 1/ Ne 1/2 28 - 209 //68	Artesian flow gan, min. with ft. drawdown after hrs.
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis made? ☐ Yes ☑ No
8 25 25 E 2635 feet from North	(12) WELL LOG
Quarter Corner of Section 28	(12) WELL LOG: Diameter of well 12 inches. Depth drilled 110 ft Depth of completed well 110 ft.
The second secon	IL.
	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
A STATE OF THE STA	MATERIAL FROM TO
TYPE OF WORK (check):	Soil 0 18
Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐	Quicksand 18 25
If abandonment, destribe material and procedure in Item 11.	Clay 25 30
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Gravel 30 70 Blue Shale 70 100
nestic Industrial Municipal Rotary Driven	Blue Shale
gation M Test Well Other Dug Bored	310001
(6) CASING INSTALLED: Threaded Welded X	100 21 100 100 100 100
(6) CASING INSTALLED: Threaded □ Welded X 12 "Diam from ft to 75 8" ft. Gage 3/8	
"Diam. from ft. to ft. Gage	the second secon
"Diam fromft. toft. Gage	
(7) PERFORATIONS: Perforated? Types II No.	B. 45. (1984)
Type of perforator water Manager	See Annual Control of the Control of
SIZE of perforations in. by 2 in.	
perforations from 40 ft. to 70 ft.	
perforations from ft. to ft.	
perforations fromft. toft.	Sec. 1 . 1 . 1 . 1 . 1 . 1 . 1 . 1 . 1 . 1
perforations fromft. toft.	
5 3	3000
Well screen installed Yes X No	
Paracturer & Tydine:	
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft, to ft.	Work started May 9 19 57 Completed June 15 19 57
CONSTRUCTION:	2) compresed outle 1) 193
well gravel packed? Yes No Size of gravel:	(13) PUMP:
Gravel placed from	Manufacturer's Name Jacuzzi Type: Turbin #P 15
Was a surface seal provided? Tes No To what depth?ft.	Type: TUPDIN H.P. 15
Material used in seal-	Well Driller's Statement:
Did any strata contain unusable water? Yes No Yee of water? Depth of strata	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Jethod of seeling strate off	
(10) WATER LEVELS:	NAME H. A. Sevey (Person, firm, or corporation) (Type or print)
itatic level 20 ft. below land surface Date	Address Rt. 1 Box 176 Vale, Oregon
Artesian pressure hbs. per square inch Date	
	Driller's well number
log Accepted by:	[Signed]
Signed] Date, 19	License No. 17 (Well Driller) License No. 17 Deta August 10 10 57
يد ي ي	License No. 17 Date August 10, 19 57