NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE OF OREGON

State Well No. SEP 101980

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

(Please type or print) (Do not write above WiAILER RESOURCES SEP Permit No.

	SALEM. OREGON			
(1) OWNER:	(10) LOCATION OF WELL:			
Name Gum Creek Farms, Inc/Heid Bros.	County Malheur Driller's well number 80-4			
Address Jamieson, Or.	SE 14 SW 14 Section 6 T. 16S R. 43E W.M.			
97909	Bearing and distance from section or subdivisi			
(2) TYPE OF WORK (check):			-	
New Well Deepening □ Reconditioning □ Abandon □				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 110			
Botery Driven Domestic Industrial Municipal	Static level 110 ft. below land	surface.	Date3/	
. ; XCX Jetted □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □	Artesian pressure lbs. per squar			
) CASING INSTALLED: Threaded □ Welded M 12 "Diam. from 0 ft. to 106 ft. Gage 250	(12) WELL LOG: Diameter of well below casing 12 Depth drilled 650 ft. Depth of completed well 650 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated.			
) PERFORATIONS: Perforated? ☐ Yes ☐ No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.			
Type of perforator used	MATERIAL	From	То	SWL
Size of perforations in. by in.	Top soil	<u> </u>	4	
perforations from	Clay, brown Gravel, medium	28	<u>28</u> 38	
perforations from	Sand. brown. fine	38	110	
perforations from	Sandstone, brown, water-	110	197	110
(7) SCREENS: Well screen installed? Yes No	bearing		1.77	
Manufacturer's Name	Clay, blue	197	235	110
Type Model No.	Clay, brown	235	245	110
Diam, Slot size Set from ft. to ft.	Clay, blue	245	275	110
Diam. Slot size Set from ft. to ft.	Clay, blue	275	400	110
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Clay, blue, hard, fractured	400	510	110
a pump test made? Yes No If yes, by whom?	Clay, blue, gravel, sand	510	530	110
'd: gal./min. with ft. drawdown after hrs.	Sand, brown-gray, fine	530	535	110
" " "	Clay, green	535	610	110
" 119 " "	Gravel, fine, multi-	610	623	110
r test /5 gal./min. with tt. drawdown after / hrs.	colored	607		
Supplemental Street Control of	Clay, green	623	650	110_
sian flow g.p.m. 2-inperature of water 64Depth artesian flow encounteredft.	Work started 3/4 19 80 Complete	. 7	/25	
Temperature of water Oppopul artisant now encountered				19 80
(9) CONSTRUCTION:	Date well drilling machine moved off of well		/25	19 80
Well seal—Material used Cement Well sealed from land surface to 18 ft. Diameter of well bore to bottom of seal 12 in. Diameter of well bore below seal 16 in.	Drilling Machine Operator's Certification: This well was constructed under my Materials used and information reported best knowledge and belief.	above a	are true	to my
Number of sacks of cement used in well sealsacks	(Signe Wester H. Bournam (Drilling Machine Operator)	. ج . ate	<i>a</i> .U	., 19.80
How was cement grout placed? with grout pump	Drilling Machine Operator's License No.	1.4	06	•
	Water Well Contractor's Certification:			
· · · · · · · · · · · · · · · · · · ·	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was a drive shoe used? X Yes □ No Plugs Size: location ft. Did any strata contain unusable water? □ Yes □ No	Name PIONEER WATER DEVELOPMENT INC. (Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address Rt. 3 Box 493 Ontari			7914
Method of sealing strata off	(S = 0.6			A
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	[Signed] Water Well Control	actor)		••••••
Gravel placed from ft. to ft.	Contractor's License No748 Date	-2/	*******	1980
, , , , , , , , , , , , , , , , , , , ,	. San the same of			