## WATER WELL REPORT STATE OF OREGON



## RECEIVED State Well No.

WATER RES URState Permit No. J. L. UNIEGON

(1) OWNER:	(10) LOCATION OF WELL:
Name CITY OF ADRIAN	County MAT.HETTR Driller's well number
Address	NW 4 SW 4 Section 14 T. 21 R. 46 W.M.
City ADRIAN OREGON 97901 State	Tax Lot #9200 Lot Blk Subdivision
(2) TYPE OF WORK (check):	Address at well location:
New Well X Deepening Reconditioning Abandon   Reconditioning Abandon   Reconditioning Abandon   Reconditioning 12.	(11) WATER LEVEL: Completed well.
<del>**</del>	Depth at which water was first found 340 ft.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Static level 11 ft. below land surface. Date 2/05/8
Rotary Air M. Driven Domestic   Industrial   Municipal X	Artesian pressure lbs. per square inch. Date
Rotary Mud   Dug   Irrigation   Test Well   Other      Bored   Thermal: Withdrawal   Reinjection	7.011
	Diameter of well below casing
(5) CASING INSTALLED: Steel IN Plastic Introduced IN Welded IN	Formation: Describe color, texture, grain size and structure of materials; and show
Threaded Welded X0	thickness and nature of each stratum and aquifer penetrated, with at least one entry
14. Diam from 10 ft. to 38 ft. Gauge 250	for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
LINER INSTALLED:	MATERIAL From To SWL
	Top Soil 0 2
(6) PERFORATIONS: Perforated? ☐ Yes XNo	Brown Sand Clay 2 35
Type of perforator used	Sandy Blue Clay 35 152
Size of perforations 1 in by in.	Blue Sandstone   152   155
perforations from ft. to ft.	Blue Clay 155 240
perforations from it. to it.	Sandy Blue Clay 240 320
perforations from it. to it.	Blue Sandstone 320 340
perforations from tt. to tt.	Blue Sand, Medium 340 375 11
(7) SCREENS: Well screen installed?   Yes X No	
Manufacturer's Name	
Type Model No	
Diam. Slot Size Set from ft. to ft.	
Diam. Slot Size Set from ft. to ft.	
Drawdown is amount water level is lowered	
below static level	
a pump test made% Larges No If yes, by whom?	
d: gal./min. with ft. drawdown after hrs.	
II I I I I I I I I I I I I I I I I I I	and the second s
Air test 250 gal/min. with drill stem at 350 ft. 4 hrs.	
Bailer test gal./min. with ft. drawdown after hrs.	
esian flow gg.m. It. drawdown after nrs.	100 - 100 -
mperature of water Depth artesian flow encountered ft.	Work started 2/02/82 19 Completed 2/05/82 19
(9) CONSTRUCTION: Special standards; Yes \(\sigma\) No\(\frac{\fir}{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frac{\frace\f{\frac{\frac{\frac{\frac{\frac{\fracc}\frac{	Date well drilling machine moved off of well 2/05/82 19
Well seal—Material used CEMENT	Drilling Machine Operator's Certification:
Well sealed from land surface to	•
Diameter of well bore to bottom of seal $\frac{1}{1}$ in.	This well was constructed under my direct supervision. Materials used and information reported above true to my best knowledge and belief.
Diameter of well bore below seal	[Signed] // 10/10 82
Number of sacks of cement used in well seal 12 sacks	(Drilling Machine Operator)
How was cement grout placed?	Drilling Machine Operator's License No. 65
PRESSURE GROUTED	Water Well Contractor's Certification:
A consequent	This well was drilled under my jurisdiction and this report is true to
Was pump installed?	the best of my knowledge and belief.
Was a drive shoe used? XXYes □ No Plugs	Name PAGE BROTHERS DRILLING
Did any strata contain unusable water? Yes XXNo	(Person, firm or corporation)  Address RT 2 BOX 4045 VALE OREGON 97918
Type of Water? depth of strata	Address A1 2 BOA 4045 VALE GON 97910
Method of sealing stratu off	[Signed] Manfield Stay
Was well gravel packed 2 · □ Yes Ki No Size of gravel:	(Water Well Contractor) 2/10/19 82
Gravel placed from	Contractor's License No