


NOTICE TO WATER WELL CONTRACTOR
The original and first copy of the report are to be filed with the...

RECEIVED WATER WELL REPORT

WATER RESOURCES DEPARTMENT
SALEM, OREGON
within 30 days from the date of well completion.

STATE OF OREGON
(Please type or print)

State Well No. 215/46 E-15da
State Permit No. _____



SALEM, OREGON

(1) OWNER: Name Adrian City
Address Adrian Oregon

(10) LOCATION OF WELL:
County Malheur Driller's well number
N.E 1/4 S.E 1/4 Section 15 T. 21 R. 46 W.M.
Bearing and distance from section or subdivision corner

(2) TYPE OF WORK (check):
New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(11) WATER LEVEL: Completed well.
Depth at which water was first found 388 ft.
Static level 4 ft. below land surface. Date 10-23-78
Artesian pressure lbs. per square inch. Date

(3) TYPE OF WELL: Rotary Driven
Cable Jetted Dug Bored
(4) PROPOSED USE (check): Domestic Industrial Municipal
Irrigation Test Well Other

(12) WELL LOG: Diameter of well below casing 8
Depth drilled 536 ft. Depth of completed well 536 ft.

CASING INSTALLED: Threaded Welded
" Diam. from 8 ft. to 6 ft. Gage 250
" Diam. from 6 ft. to 0 ft. Gage
" Diam. from 0 ft. to 0 ft. Gage

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

PERFORATIONS: Perforated? Yes No.
Type of perforator used
Size of perforations 1/2 in. by 1/2 in.
perforations from 0 ft. to 0 ft.
perforations from 0 ft. to 0 ft.
perforations from 0 ft. to 0 ft.

MATERIAL	From	To	SWL
sticky clay	0	42	
Blue shale	42	388	
Coarse black sand	388	408	
Fine sand & shale	408	432	
Fine Sand stone & clay	432	536	

(7) SCREENS: Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

Work started 10-18-78 19 Completed 10-23-78 19
Date well drilling machine moved off of well 10-24-78 19

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom? Page Bros
Yield: 55 gal./min. with 395 ft. drawdown after 13 hrs.
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 76 Depth artesian flow encountered ft.

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Winfield Page Date 11-2-78, 19
(Drilling Machine Operator)
Drilling Machine Operator's License No. 65

(9) CONSTRUCTION:
Well seal—Material used Cement
Well sealed from land surface to 27 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 5 sacks
How was cement grout placed? Pressure grouted
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name PAGE BROTHERS DRILLING
(Person, firm or corporation) (Type or print)
Address RT. 2 BOX 371- VALE, OREGON 97918
[Signed] Winfield Page
(Water Well Contractor)
Contractor's License No. 564 Date 11-2-78, 19