NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the WATER WELL REPORT RECEIVED			
WATER RESOURCES DEPARTMENT, STATE OF OREGON SALEM, OREGON 97310 (Please type or print) WAR E 1978			
- 171 (I) I (Ficase Lybe	V/ATED DESCRIPTION State Permit N	To	
of well completion. Do not write ab	ove this line ATER RESOURCES DEPT		
(1) OWNER I	SAI FM, ORECOM		
(1) OWNER:	(10) LOCATION OF WELL:		
Nameity of Adrian	County Malheur Driller's well no	umber	
Address Adrian, Oregon	S.W 34 S.W34 Section 15 T. 21	r. 46 w.m.	
	Bearing and distance from section or subdivisi	on corner	
(2) TYPE OF WORK (check):			
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐		7	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	11	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	-		
Rotary A Driven D	Depth at which water was first found 163 ft.		
Cable	Static level 160 ft. below land s	surface. Date 2-14-78	
Dug Bored I Irrigation Test Well Other	Artesian pressure lbs. per squar	e inch. Date	
CASING INSTALLED: Threaded [], Welded [5]	(12) WELL LOG: Diameter of well below casing		
"Diam. from tt. to ft. Gage	Depth drilled 228 ft. Depth of compl	eted well 228 ft.	
" Diam. from	Formation: Describe color, texture, grain size	and structure of materials:	
Dami ton It of Gage	and show thickness and nature of each stratu with at least one entry for each change of forma	m and aquifer penetrated	
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	cipal water-bearing strata.	
Type of perforator used	MATERIAL	From To SWL	
Size of perforations in. by in.	Top Soil	0 18	
perforations from ft. to ft.	Sandstone	18 21	
perforations from ft. to	Sandy Yellow Clay	21 75	
perforations from	Med. Sand	75 83	
	Sandy Yellow Clay	83 93	
Well screen installed? Yes No	Med. Sand	93 96	
Manufacturer's Name	Yellow Clay	96 110	
Type Model No.	Sand & Pea Gravel	110 111	
Diam Slot size Set from ft. to ft	Yellow Clay	11/1 160	
Diam. Slot size Set from ft. to ft.	Coarse Sand W/B(5 gpm.)	160 163	
(8) WELL TESTS: Drawdown is amount water level is	Dark Sandstone	163 184	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Fractured Sandstone W/B	184 188	
Was a pump test made? Yes TyNo If yes, by whom?	Blue Sandstone (60 gpm)	188 190	
Yield: gal./min. with ft. drawdown after hrs.	Soft Sandstone (90 gpm)	190 194	
	Blue Soft sandstone	19/1 228	
A design of the second of the	<u> </u>		
Page 4-4 100			
Bailer test 100 gal./min. with 48 ft. drawdown after hrs.			
Artesian flow g.p.m.			
perature of water 65 Depth artesian flow encountered ft.	Work started 2-10-78 19 Complete	d 2-15-78 19	
(9) CONSTRUCTION: 1	Date well drilling machine moved off of well	2-15-78 19	
		L L) (0 18	
Well seal-Material lised munu	Drilling Machine Operator's Certification:	71	
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported	direct supervision.	
Diameter of well bore to bottom of sealin.	best knowledge and belief.	and to take to my	
Diameter of well bole below seal in.	[Signed] MANULEUTER	Date 2-22-7819	
Number of sacks of tement used in well seal sacks	Drining Machine Operator		
How was cement grout placed?	Drilling Machine Operator's License No		
The state of the s	Water Well Contractor's Certification:		
		Man and Harry	
The state of the s	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Page Bros. Drilling		
Did any strata contain unusable water? Yes XNo	(Person, firm or corporation)	(Type or print)	
Type of water? 1 depth of strata	Address Rt. 2 Box 371 Vale.	Orezon 97918	
Method of sealing strata off	01. 110/2	2	
Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well Contra	ctor)	
Gravel placed from ft.	Contractor's License No. 564 Date 2		
(USE ADDITIONAL SHE			