

RECEIVED

WATER WELL REPORT

STATE ENGINEER SALEM, OREGON 97310
within 30 days from the date
of well completion.

DEC 12 1977

STATE OF OREGON
(Please type or print)

WATER RESOURCES DEPT. (above this line)

SALEM, OREGON

State Well No. 22S/46E-36cd

State Permit No.

(1) OWNER:

Name PORTER LEE
Address ADRIAN OREGON

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED:

Threaded ☐ Welded ☒
6" Diam. from 41 ft. to 39 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name

Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

Ball test 3 gal./min. with 0 ft. drawdown after 1 hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used DRILLING MUD

Well sealed from land surface to 30 ft.

Diameter of well bore to bottom of seal 8 in.

Diameter of well bore below seal 6 in.

Number of sacks of cement used in well seal sacks

Number of sacks of bentonite used in well seal sacks

Brand name of bentonite

Number of pounds of bentonite per 100 gallons
of water lbs./100 gals.

Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County MAINEUR Driller's well number

SE 1/4 SW 1/4 Section 36 T. 22S R. 46E W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 90 ft.

Static level 38 ft. below land surface. Date 4-19-76

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6

Depth drilled 135 ft. Depth of completed well 135 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
BROWN CLAY	0	2	—
WHITE HARD PAN	2	5	—
GRAVEL WITH BROWN CLAY	5	8	—
GRAVEL WITH BROWN CLAY	11	31	—
STICKY BROWN CLAY	31	55	—
STICKY BLUE CLAY	55	90	—
GRAVEL WITH BLUE CLAY	90	91	38
STICKY BLUE CLAY	91	135	38
BLUE CLAY	135		

Work started APRIL 15 1976 Completed APRIL 19 1976

Date well drilling machine moved off of well APRIL 19 1976

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] Daniel M. [Signature] Date 4-22, 1976

(Drilling Machine Operator)

Drilling Machine Operator's License No. 286

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name METZER WELL DRILLING

(Person, firm or corporation)

(Type or print)

Address HOMERIDGE ROAD

[Signed] Daniel M. [Signature]

(Water Well Contractor)

Contractor's License No. 399 Date April 22, 1976