NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT.
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

Malh 007
Malh 007
State Well No. 135 42E-20ab

State	Permit	No.	

(1) OWNER: Sumpter Gold Oredge, Inc.	(10) LOCATION OF WELL:	^		
Name % LLOYD DINGER	County Driller's well nu			
Address Box 410	NW 14 NE 14 Section 20 T. 135	R. 47	<u> </u>	W.M.
Haines ORP	Bearing and distance from section or subdivision	on corner	•	
(2) TYPE OF WORK (check):				
New Well Deepening Reconditioning Abandon				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found		16	50 ft.
Rotary Driven Domestic Industrial Municipal	Static level 48 ft. below land s	urface. J	Date	
Cr	Artesian pressure lbs. per squar	e inch. I	Date	
CASING INSTALLED: Threaded Welded 7	(12) WELL LOG: Diameter of well to Depth drilled 650 ft. Depth of complete the depth of	eted well	65	2 ft.
	Formation: Describe color, texture, grain size a and show thickness and nature of each stratus with at least one entry for each change of format	m and action. Repo	quifer pe ort each	enetrated, change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	r		
Type of perforator used	MATERIAL	From	49	SWL
Size of perforations in. by in.	Clay & GRavel	0	110	
perforations from	BESALT BLOCK	110	160	
perforations from	CLay + GRR2 VCL	160		285 15
perforations from ft. to ft.	White Rock	285	325	30
(7) SCREENS: Well screen installed? Yes No	CLAY 4 GREVEL	325	595	
Manufacturer's Name	GREEN SORPSTONE	595	640	
Type Model No.	BROWN BESZLT /GER/SS	640	650	600G
Diam. Slot size Set from ft. to ft.				
Diam. Slot size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Augh test made? If Yes No If yes, by whom? DRILLER	The State of Cases			
700	DEC 2 1 1980			
i: 300 gal./min. with 390 ft. drawdown after 1 hrs.	UE. O STATE			
,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,,	WATER RESOURCES DEPT			
n " " "	SALEM, OREGON	\longrightarrow		
r test gal./min. with ft. drawdown after hrs.				
dan flow g.p.m.		<u> </u>		<u> </u>
remperature of water Depth artesian flow encountered ft.	Work started 7-25-80 19 Complete	ed 8	<u>~/3 -</u>	-8G3
(9) CONSTRUCTION:	Date well drilling machine moved off of well	<u>8-1</u>	<u>3–81</u>	<u>) 19</u>
Well seal—Material used PORT22ND CMENT Well sealed from land surface to 1/8 ft. Diameter of well bore to bottom of seal in. Diameter of well bore below seal 12 in. Number of sacks of cement used in well seal 46 sacks	(Drilling Machine Operator)	above a	are true	
How was cement grout placed? TREMIC	Drilling Machine Operator's License No.		56	
	Water Well Contractor's Certification:			
	This well was drilled under my jurisd	iction an	d this	report is
Was a drive shoe used? Yes No Plugs Size: location ft.	true to the best of my knowledge and bel		0,00	2.
Did any strata contain unusable water? Yes	Name (Person firm or corporation)	(Ty	pe or pri	int)
Type of water? depth of strata	Address Phaleton Off	t 	•••••	*******
Method of sealing strata off	I some And Basel			
Was well gravel packed? Yes Ano Size of gravel:	[Signed] (Water Well Control	ractor)	**********	
	Contractor's License No. 544 Date	8	- 16	1980