NOTICE TO WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED
MAR 27 1972
STATE ENGINEER
SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

Mark 713

State Well No. 18/41-16ad

State Permit No.

(1) OWNER:
Name Grady Romans
Address West Fall, Oregon

(2) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☑ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☑ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☑
12" Diam. from 0 ft. to 40 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☑ Yes ☐ No.
Type of perforator used factory
Size of perforations 1/4 in. by 4 in.
960 perforations from 20 ft. to 40 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☑ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☑ Yes ☐ No If yes, by whom? Page Bros.
Yield: 100 gal./min. with 30 ft. drawdown after 6 hrs.
" " "
" " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 52° Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 16 in.
Diameter of well bore below seal 12 in.
Number of sacks of cement used in well seal 2 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☐ Yes ☑ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☑ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☑ Yes ☐ No Size of gravel: 3/4 +
Gravel placed from 20 ft. to 30 ft.

(10) LOCATION OF WELL:
County Malheur Driller's well number
SE ¼ NE ¼ Section 16 T. 18 R. 41 W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 16 ft.
Static level 12 ft. below land surface. Date 2-20-72
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 12
Depth drilled 45 ft. Depth of completed well 45 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Sandy Clay	0	10	
Sand & Silt	10	20	12
Sand & fine gravel	20	35	
Cinderpite	35	40	
Blue Clay	40	45	

Work started 2-10 1972 Completed 2-20 1972
Date well drilling machine moved off of well 2-21 1972

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] W. L. Page (Drilling Machine Operator) Date 2-22 1972
Drilling Machine Operator's License No. 65

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Hysell's Drilling (Person, firm or corporation) (Type or print)
Address 365 Main St. N. Vale, Ore.
[Signed] [illegible] (Water Well Contractor)
Contractor's License No. 396 Date 2/21 1972

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119