WATER WELL REPORT STATE OF OREGON



AZGEIYED

State Well No.

PLEASE TYPE OF PRINT IN THE SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:	
Name FRED KUWAHARA	County MALHEUR Driller's well number	
Address FOOTHILL DRIVE	N.W 4 S.W 4 Section 14 T. 18 R. 45 W.	<u>M.</u>
City VALE, OREGON 97918 State	Tax Lot #2701 Lot Blk Subdivision	
(2) TYPE OF WORK (check):	Address at well location:	
New Well♥ Deepening □ Reconditioning □ Abandon □	(11) WATER TEVEL Completed well	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well. Depth at which water was first found 25	_
(3) TYPE OF WELL: (4) PROPOSED USE (check):	0.3	4 -8
	Static level 12 ft. below land surface. Date 9-2. Artesian pressure lbs. per square inch. Date	<u> </u>
Rotary Mud Dug Irrigation Test Well Other		
☐ Bored ☐ Thermal: Withdrawal ☐ Reinjection ☐	(12) WELL LOG: Diameter of well below casing	 ft.
CASING INSTALLED: Steel X Plastic C	Depth drilled 35 ft. Depth of completed well 35 Formation: Describe color, texture, grain size and structure of materials; and sh	
Threaded Welded X 7 Diam from +1 ft. to 34 ft. Gauge 250	thickness and nature of each stratum and aquifer penetrated, with at least one ent	try
"Diam from ft. to ft. Gauge	for each change of formation. Report each change in position of Static Water Levand indicate principal water-bearing strata.	vei
LINER INSTALLED:	MATERIAL From To SWL	
	SANDY CLAY 0 25	
" Diam. from	MED. GRAVEL 25 34	_ `
(6) PERFORATIONS: Perforated? X Yes □ No	BLUE CLAY 34 35	
Type of perforator used TORCH Size of perforations 4 in. by 5 in.		
Size of perforations 4 in. by in. 30 perforations from 29 ft. to 34 ft.		
perforations from		
perforations from ft. to ft.		
(7) SCREENS: Well screen installed? ☐ Yes ☐XNo		
Manufacturer's Name		
Diam. Slot Size Set from ft. to ft.		
Diam. Slot Size Set from ft. to ft.		
Drawdown is amount water level is lowered		_
2000 20000		
Was a pump test made?		
ed: gal./min. with ft. drawdown after hrs.		
50 30 1		
Air test O gal./min. with drill stem at JO ft. 1 hrs. Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
mperature of water 56 Depth artesian flow encountered ft.	Work started 9-24 19 83 Completed 9=24 19	33
(9) CONSTRUCTION: Special standards: Yes \(\text{N} \)	Date well drilling machine moved off of well 9-24 19	33
Well seal—Material used CEMENT	(unbonded) Water Well Constructor Certification (if applicable	 :
Well sealed from land surface to 24 ft.	This well was constructed under my direct supervision. Materials u	
Diameter of well bore to bottom of sealin.	and information reported above are true to my best knowledge and beli	lef. えて
Diameter of well bore below seal in.	[Signed]	<u>.ر.</u> د
Number of sacks of cement used in well seal 7 sacks	Bonded Water Well Constructor Certification:	
How was cement grout placed? PRESSURE GROUTED	Bond #U458259 Issued by: UNITED PACIFIC INS. (number) Surety Company Name	<u>•</u>
	This well was drilled under my jurisdiction and this report is true	e to .
TV	the best of my knowledge and belief. NamePAGE BROTHERS DRILLING	
Was pump installed?		012
Did any strata contain unusable water? Yes XNo	Address RT 2-BOX 4045-VALE OREGON or 970	710
Type of Water? depth of strata	[Signed]////////////////////////////////////	
Method of sealing strata off	Water Well Constructor	·····
Was well gravel packed? ☐ Yes ☐ Yo Size of gravel:	Date 1.0-1.1, 19. &	33
Gravel placed from ft. to ft.		