## WATER WELL REPORT MALE JUL 2 3 130. STATE OF OREGON GO WATER RESOURCES DEPT PLEASEM, POREGON IN IN

PLEASEM, POREGONT IN INK

per: Md.	185/45E-20
State Well No.	18= 18= 2081

	/	
State Permit No.	**************************	

(1) OWNER:	(10) LOCATION OF WELL:	:
Name OREGON TRAIL MUSHROOM COMPANY	County MALHUER Driller's well number	1 +
Address	SE 4 SE 4 Section 20 T. 18 R. 43	W.M.
City Ontain State Oce,	Tax Lot # Lot Blk Subdivi	
(2) TYPE OF WORK (check):	Address at well location:	
New Well ■ Deepening □ Reconditioning □ Abandon □		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
	Depth at which water was first found	5 ft.
2000	Static level 5 ft. below land surface. Da	ite 5-21
Rotary Air Driven Domestic Industrial Municipal Rotary Mud Dug Irrigation Test Well Other	Artesian pressure lbs. per square inch. l	Date
Bored	(12) WELL LOG: Diameter of well below casing	12 in
CASING INSTALLED: Steel Plastic	Depth drilled 200 ft. Depth of completed well	
Threaded  Welded	Formation: Describe color, texture, grain size and structure of mater	rials; and show
	thickness and nature of each stratum and aquifer penetrated, with at for each change of formation. Report each change in position of Stat	least one entry tic Water Level
"Diam. from	and indicate principal water-bearing strata.	
LINER INSTALLED:	MATERIAL From To	o SWL
ft. Gauge	Soil Silt 05	
(6) PERFORATIONS: Perforated? ☐ Yes ¥ No	Silt Blue Grav Sand 5 12	2
Type of perforator used	Small Boulders sand &	
Size of perforations in. by in.	gravel 12 ac	5 5'2"
perforations fromft. toft.	Light gray clay 20 28	3
perforations fromft. toft.	Gray clay Hard 22 15	54'10'
perforations from	Gray clay fractured 155 20	10 41
(7) SCREENS: Well screen installed? ☐ Yes ☑ No		
Manufacturer's Name		
Type		
Diam. Slot Size Set from ft. to ft.  Diam. Slot Size Set from ft. to ft.		
Duamless is assessed to 1 - 12 1 - 1		
(8) WELL TESTS:  Drawdown is amount water level is lowered below static level		
Was a pump test made? $\square$ Yes $\square$ No If yes, by whom? $DRILLER$		
.: 6 O gal/min. with 57 ft. drawdown after 34 rs.		
II		
Air test gal./min. with drill stem at ft. hrs.		
Bailer test gal/min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
perature of water 💮 Depth artesian flow encountered ft.	Work started 5-3/1984 Completed 5-3	1 1984
(9) CONSTRUCTION: Special standards: Yes  No Y	Date well drilling machine moved off of well 5-3	1 1984
Well seal-Material used Portland Cement	(unbonded) Water Well Constructor Certification (if a	nnlicable).
Well sealed from land surface to	This well was constructed under my direct supervision. M	
Diameter of well bore to bottom of seal	and information reported above are true to my best knowledg	e and belief.
Diameter of well bore below seal	[Signed] Date	, 19
Number of sacks of cement used in well sealsacks	Bonded Water Well Constructor Certification:	
How was cement grout placed? Grout pump	Bond/2- 7933149 Issued by: MILLER GROW	ip or Texa
1 7	(number) Surety Company Name	e ()
	This well was drilled under my jurisdiction and this rep the best of my knowledge and belief.	ort is true to
Was pump installed?	Name BOWMAN DRILLING	***********
Was a drive shoe used? ☐ Yes No Plugs Size: location ft.	(Person, firm or corporation)	Type or print)
Did any strata contain unusable water?   Yes X No  Type of Water?  double of strate	Address O. BOX 41 113/11280N OR	<b>C</b>
Type of Water? depth of strata  Method of sealing strata off	[Signed] Bester H. Bournan	<u> </u>
	Water Well Constructor	P 19 84
Was well gravel packed? ☐ Yes Yoo Size of gravel:	Date	a , 19 <i>9. J</i>
District places it that the interest it. W	4	