

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

RECEIVED WATER WELL REPORT STATE OF OREGON JUL 28 1970 STATE ENGINEER SALEM, OREGON

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF OREGON (Please type or print)

STATE ENGINEER SALEM, OREGON

10004 MAR 29 / 2W 25ab State Well No. State Permit No. G 5400

(1) OWNER:

Name Mr. & Mrs. Peter Threlkel Address Rte. 1, Turner, Ore.

(2) TYPE OF WORK (check):

New Well [] Deepening [x] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven [] Cable [x] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Irrigation [x] Test Well [] Other []

(5) CASING INSTALLED:

Threaded [] Welded [x] 8" Diam. from 0 ft. to 84 ft. Gage 250

(6) PERFORATIONS:

Perforated? [x] Yes [] No. Mills Size of perforations 300 perforations from 84 ft. to 32 ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [x] Yes [] No If yes, by whom? Self Yield: 325 gal./min. with 13 ft. drawdown after 1 hrs. 225 " 7 " 1 "

CONSTRUCTION:

Well seal—Material used Existing Bentonite seal Well sealed from land surface to Existing ft. Diameter of well bore to bottom of seal 8 in. Diameter of well bore below seal 8 in. Number of sacks of cement used in well seal Existing sacks Number of sacks of bentonite used in well seal Existing sacks Brand name of bentonite National Number of pounds of bentonite per 100 gallons of water Existing seal lbs./100 gals. Was a drive shoe used? [x] Yes [] No Plugs Size: location ft. Did any strata contain unusable water? [] Yes [x] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Marion Driller's well number 445 NW 1/4 SE 1/4 Section 23 T. 9S R. 2W W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 32 ft. Static level 5 ft. below land surface. Date 7/24/70 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing Depth drilled 84 ft. Depth of completed well 84 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows: Existing well, Packed cobbles & gravel, Layered soft silted, Packed cobbles & gravel, Layered soft silted.

30' because it is a deepened well

Work started 7/22/70 19 Completed 7/24/70 19 Date well drilling machine moved off of well 7/24/70 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Pete Tolmasoff Date 7/27, 19 70 (Drilling Machine Operator)

Drilling Machine Operator's License No. 320

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Pete Tolmasoff Well Drilling (Person, firm or corporation) (Type or print)

Address Turner, Ore.

[Signed] Pete Tolmasoff (Water Well Contractor)

Contractor's License No. 410 Date 7/27/70, 19