NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT: 10 1967

STATE OF OREGON: ENGINEER Well No. 4/1w-35M
(Please type or Print) G-3977 (State Permit No.

(1) OWNER:	(11) WELL TESTS: Drawdown is amount volume to lowered below static lev	rel	1.10
Name JOHN GARBER	Was a pump test made? Yes \[\] No If yes, by whom		
Address RT. I BOX 225A	Yield: 250 gal./min. with T09 ft. drawdow	_	
HUBBARD OREGON 97032	<u>" 200 " 58 "</u>	8	
(2) LOCATION OF WELL:	" I40 " 49 "	8	3
~~~4	Bailer test gal./min. with ft. drawdown after hrs.		
County MARION Driller's well number I204	Artesian flow g.p.m. Date		
1/4 Section T. 4S R. R I W W.M.	Temperature of water Was a chemical analysis n	nade? 🔲 Y	es 🗌 No
Bearing and distance from section or subdivision corner BEGINNING AT A POINT ON THE NORTH	(12) WELL LOG: Diameter of well below case	sin <b>g</b>	
POTENDARY TIME OF THE A.R. DAMICH & WIFE	Depth drilled 200 ft. Depth of completed wel	1 200	ft.
.C. 14.64 CHAINS EAST OF THE NW. CURNE	Formation: Describe by color, character, size of material show thickness of acuiters and the kind and nature of t	and struc he materi	cture, and al in each
F SAID CLAIM; THENCE SOUTH TO 6 WEST 16	stratum penetrated, with at least one entry for each ch	lange of f	ormation.
AINS, THENCE E. 15.63 CHAINS; THENCE N. IC	W MATERIAL	FROM	TO
(3) TYPE OF WORK (check) 15 63 CHAINS TO PLA	ŬĒ.		
New Well Deepening Reconditioning Abandon	TOP SOIL	0	2
andonment, describe material and procedure in Item 12.	BROWN CLAY	2	20
	BROWN SANDY SILT	20	55
(4) PROPOSED USE (check): (5) TYPE OF WELL:	GRAY SANDY CLAY	55	80
Domestic ☐ Industrial ☐ Municipal ☐ Rotary ☐ Driven ☐ ☐ Cable ☐ ☐ Jetted ☐	BLACK SAND	80	IOO
Irrigation T Test Well □ Other □ Dug □ Bored □	BLACK SAND & GRAVEL	IOO	I04
		I04	135
(6) CASING INSTALLED: Threaded	GRAY CLAY & SAND CLAY & GRAVEL	I35	I50
IO	BLACK SAND & GRAVEL	I50	I80
ft. toft. Gage	GRAY CLAY	I80	<u> 190</u>
ft. Gage			
(7) PERFORATIONS: Perforated?  \( \textbf{K} \text{Yes}  \text{No} \)	BLACK SAND & GRAY CLAY	I90	<u> 195</u>
	GRAY CLAY	I95	_200_
Type of perforator used MILLS Size of perforations 2 in. by 3/8 in.			
		1	
40   perforations from   103   ft. to   105   ft.   280   perforations from   150   ft. to   170   ft.		Hi	
perforations from		<del>  </del>	
perforations from			
perforations from ft. to ft.			
perforations from ft. to ft.	1 1,	-	
(8) SCREENS: Well screen installed? ☐ Yes 🛣 No			
Manufacturer's Name			
Model No.		4	
A Slot size Set from ft. to ft.	Work started MARCH II 1967 Completed A	PRII.	3 1967
Diam. Slot size Set from ft. to ft.	Date well drilling machine moved off of well APRIL 6 19679		
(9) CONSTRUCTION:	(13) PUMP:	<u> </u>	30 F
	(15) 1 CM1.		
Well seal-Material used in seal CEMENT & PUDDLE CLAY	Manufacturer's Name		
Depth of seal20ft. Was a packer used?	Type: H.P.		
Diameter of well bore to bottom of seal in.	Water Well Contractor's Certification:		
Were any loose strata cemented off? Tyes In No Depth	Waster Work Constitution & Constitution.		
Was a drive shoe used? ☐ Yes ☐ No 🏯	This well was drilled under my jurisdiction and this report is		
Was well gravel packed?   Yes No Size of gravel:	true to the best of my knowledge and belief.		
Gravel placed fromft. toft.	NAME WILLAMFTTE DRILLING CO (Person, firm or corporation) (Type or print)		
Did any strata contain unusable water? Tes I No			
Type of water? depth of strata	Address RT. 2 BOX 276 SALEM, OREGON 97303		
Method of sealing strata off	Drilling Machine Operator's License No		
(10) WATER LEVELS:	Straing Machine Operator's License No. 151		
572 E	[Signed] (Water Well Contractor)		
inch Date		TT ~	Town
	Contractor's License No	TTQ	T218:1/
(USE ADDITIONAL S	HEETS IF NECESSARY)		