MARI.

The original and first copy.

Of this report are to be in 10 14 1965

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the later TE ENGINE (Flease type or print)

of well completion.

35 C 4/160 / 万

G-3722

State Permit No.

1) OWNER: SALEM ORGGON	(11) WELL TESTS: Drawdown is amount water level is lowered below static level		
Name Stauffer Bres.	Was a pump test made? Yes 🖂 No If yes, by whom?	dril	ler
Address Hubbard, Oregon	Yield: 400 gal./min. with 81 ft. drawdow	n after	6 hrs.
The second secon	<u> </u>		6 "
(2) LOCATION OF WELL:	1)))		
County Marian Driller's well number	Bailer test gal./min. with ft. drawdo	wn after	hrs.
County Marian Driller's well number 34 Section 26 T. 4S R. 1W W.M.	Artesian flow g.p.m. Date Temperature of water Was a chemical analysis r	nadas 🖂 🖰	Vec 🖃 No
Bearing and distance from section or subdivision corner			
The state of the s	(12) WELL LOG: Diameter of well below or	sing	
The second secon	Depth drilled 136 ft. Depth of completed we		136 ft.
では、「中国では、100mmのでは、	Formation: Describe by color, character, size of materia show thickness of aquifiers and the kind and nature of stratum penetrated, with at least one entry for each c	l and stru the mater hange of	cture, and ial in each formation.
で、一般では、「「「「「「「」」」」では、「「「「」」」では、「「「」」」では、「「」」」では、「「」」」では、「「」」」では、「「」」」では、「「」」」では、「「」」」では、「「」」」では、「「」」」では、「「」」では、「」」では、「」」では、「「」」では、「「」」では、「「」」では、「「」」では、「」」では、「「」」では、「」」では、「「」」では、「」」では、「」」では、「」」では、「」」では、「」」では、「「」」では、「」では、「	MATERIAL	FROM	TO
(3) TYPE OF WORK (check):	Surface	0	3
New Well X Deepening [] Reconditioning [] Abandon []	Brown sandy elay	3	43
andonment, describe material and procedure in Item 12.	Blue sandy elay	43	82
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Breken sand and gravel	82	86
Potenty [Driven [Blue sandy clay	86	92
Domestic 🗌 Industrial 🗎 Municipal 📋 Cable 📆 Jetted 🗎	Red sand	92	97
Irrigation T Test Well Other Dug Bored	Black sand	97	102
(6) CASING INSTALLED: Threaded [] Welded [Broken gravel	102	112
12 " Diam. from 0 ft. to 120 ft. Gage 14"	Blue clay	112	136
8 " Diam. from 0 ft. to 80 ft. Gage 14"		ļ	<u> </u>
"Diam. fromft. toft. Gage			
(7) PERFORATIONS: Perforated? Yes No			
Type of perforator used Millknife			
Size of perforations ½ in. by ½ in. 315. perforations from 83. ft. to 112. ft.			
315. perforations fromO. ft. toft.			<u> </u>
perforations fromft. toft.			-
perforations fromft. toft.			
perforations fromft. toft.		<u> </u>	1
perforations fromft. toft.		† · · · · · ·	1 .
(8) SCREENS: Well screen installed? ☐ Yes ■ No			
Manufacturer's Name	-		
Type Model No.	· · · · · · · · · · · · · · · · · · ·		<u> </u>
Slot size Set from ft. to ft.	Work started June 2 19 65 Completed J	uly 2	₁₉ 65
Diam. Slot size Set from ft. to ft. to ft.	Date well drilling machine moved off of well J.	uly 2	¹⁹ 65
(9) CONSTRUCTION:	(13) PUMP:		
Well seal-Material used in sealPuddled_mud	Manufacturer's Name		
Depth of sealft. Was a packer used?	Type: H.P.		
Diameter of well bore to bottom of sealin.	Water Well Contractor's Certification:		
Were any loose strata cemented off? Tyes No Depth			
Was a drive shoe used? ☐ Yes 🗷 No	This well was drilled under my jurisdiction true to the best of my knowledge and belief.	and this	report is
Was well gravel packed? Tyes I No. Size of gravel: 114-		-	
Gravel placed from 80 ft to 105 ft.	NAME John Truman Miller (Person, firm or corporation) (Tr	me or	4
Did any strata contain unusuable war? Yes No	P.O. Roy 42 Hubband One con		
Type of water? depth of strata	Address F O DOX 42 Hubbard,		
Method of sealing strata off	Drilling Machine Operator's License No27	7	**************
(10) WATER LEVELS:	I was a later of the		
Static level 34 ft. below land surface Date 7/2/65	[Signed] (Water Well Contractor)		***************************************
Artesian pressure Ibs. per square inch Date	Contractor's License No. 26 Date July	10	₁₉ 65
The state of the s	HEETS IF NECESSARY) 277	on the constitution of the	