NOTICE TO WATER WELL CONTRACTOR
The original and first copy

## WATER WELL REPORT

STATE ENGINEER, SALEM, OREGON 9320 E C VITTO OF OREGON within 30 days from the date of well completion. AUG 2.4 1999 not write above this line

State Permit No. G-7862

(1) OWNER: WATER RESOURCES DEPT.	(10) LOCATION OF WELL:			
Name William Strubahr SALEM. OREGON	County Marian Driller's well number			
Address Rte 1 Box 88	34 34 Section 35 T. 48 R. 1W W.M.			
Hubbard, Oregon 97032	Bearing and distance from section or subdivisi			
(2) TYPE OF WORK (check):	Bearing and distance from Section of Subdivisi	OII COIIIC		······································
New Well   Deepening □ Reconditioning □ Abandon □				<del></del>
If abandonment, describe material and procedure in Item 12.	(14) THE PROPERTY OF THE PROPE		5 ¥	•
	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found			ft.
Rotary  Driven  Domestic  Industrial  Municipal	Static level 31 ft. below land	surface.	Date	7/19/7′
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure — lbs. per squar	re inch.	Date	
(5) CASING INSTALLED: Threaded □ Welded ☐ 16 "Diam from 0 ft to 20 ft Gage 14" 12 "Diam from 0 ft to 114 ft Gage 14" Threaded □ Welded ☐ 14" Threaded □ Welded ☐ 16 "Diam from 0 ft to 114 ft Gage 14" Threaded □ Welded ☐ 16 "Diam from 0 ft to 114 ft Gage 16" Threaded □ Welded ☐ 16 "Diam from 0 ft to 114 ft Gage 16" Threaded □ Welded ☐ 16 "Diam from 0 ft to 114 ft Gage 16" Threaded □ Welded ☐ 16" Diam from 0 ft to 114 ft Gage 16" Threaded □ Welded ☐ 16" Diam from 0 ft to 114 ft Gage 16" Diam from 114 ft Gage 114 ft Gage 16" Diam from	(12) WELL LOG: Diameter of well  Depth drilled 114 ft. Depth of comp.  Formation: Describe color, texture, grain size and show thickness and nature of each stratu with at least one entry for each change of forma position of Static Water Level and indicate printing.	leted well and struc m and a tion. Rep	eture of requifer per	naterials; netrated, change in
Type of perforator used pre-perforated pipe	MATERIAL	From	To	swr
Size of perforations 3/16 in. by 2 in.	Soil	0	3	-
480 perforations from 95 ft. to 105 ft.	Brown Clay	3	16	
perforations fromft, toft.	Blue clay	16	55	
perforations from ft. to	Red sand	55	65	
	Blue clay	65	83	
(7) SCREENS: Well screen installed?   Yes  No	Black sand	83	86	
Manufacturer's Name	Blue clay	r186	95	
Type Model No.	Sand & gravel	95	105	
Diam. Slot size Set from ft. to ft.	Blue clay	105	114	
Diam. Slot size Set from ft. to ft.		<del>                                     </del>	ļ	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		<del>                                     </del>		
Was a pump test made? Tyes I No II yes, by whom? driller	21 7 1			
Yield: 275 gal./min. with 75 ft. drawdown after 6 hrs.	72.	1		
eau. 2) gai./min. what / 20 drawdown arest 6 ms.	्राच्या । प्राप्तिकास्य क्रिक्त क्रिक् विकास क्रिक्त	1		
" " " "				
	No. 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			
Bailer test gal./min. with ft. drawdown after hrs.	· · · · · · · · · · · · · · · · · · ·			
Artesian flow g.p.m.	and the same and t	<u> </u>		
aperature of water Depth artesian flow encountered ft.	Work started July 11 19 77Complete	ed Jul	v 19	19 77
(9) CONSTRUCTION:	Date well drilling machine moved off of well		y 19	19 77
Well seal—Material used Coment	Drilling Machine Operator's Certification:			· · · · · · · · · · · · · · · · · · ·
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported	direct	super	vision.
Diameter of well bore to bottom of sealin.	best knowledge and belief	anuve	are wile	: w my
Diameter of well bore below sealin.	[Signed] Johnson Maller	Date	ug 8	19.77
Number of sacks of cement used in well sei 8 sacks	(Prilling Mackine Operator)	06		,
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.			
Brand name of bentonite	Water Well Contractor's Certification:		:	
Number of pounds of bentonite per 100 gallons	1 ·		. 4 41. 1	•
of water lbs/100 gals, cement plug 112-114	This well was drilled under my jurisdi true to the best of my knowledge and bel	.cuon ar ief.	ia this r	eport is
Was a drive shoe used?   Yes K No Pines Size. location It.	Name John Truman Miller			,
Did any strata contain unusable water? Li Yes I No	(Person, firm or corporation)		pe or prin	•
Type of water? depth of strata	Address 1780 Tomlin Woodburn	., Ore	gon	97071
Method of sealing strata off	[Signed] John V. Millar			
Was well gravel packed? ▼ Yes □ No Size of gravel:	(Water Well Contr	actor)		m-innerentario della
Gravel placed from 20 ft, to 114 ft.	Contractor's License No. 277 Date	Aug 8	}	., 1977
(USE ADDITIONAL SH			81	*45858-119