

The original and first copy
of this report are to be
filed with the

RECEIVED WATER WELL REPORT

STATE ENGINEER, SALEM, OREGON

within 30 days from the date
of well completion.

SEP - 3 1975 STATE OF OREGON
(Please type or print)
WATER RESOURCES DEPT.
(Do not write above this line)
SALEM, OREGON

State Well No. 85/24-15
State Permit No. 6-1041L

(1) OWNER:

Name Mr. & Mrs. Del Barber
Address P.O. Box 132, Turner

(2) TYPE OF WORK (check):

New Well ☐ Deepening ☒ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED:

Threaded ☐ Welded ☒
6" Diam. from 0 ft. to 33 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.
" " "

"Air lift 40 gpm from 160' after 1hr."

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used EXISTING SEAL - OK
Well sealed from land surface to ft.
Diameter of well bore to bottom of seal in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons
of water lbs./100 gals.
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☐ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☐ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Marion Driller's well number 555 Deeven
NE ¼ SW ¼ Section 15 T. 8S R. 2W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 148 ft.
Static level 70 ft. below land surface. Date 8/5/75
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6"

Depth drilled 163 ft. Depth of completed well 163 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Existing well	0'	83'	73'
Basalt (grey hard)	83'	100'	
Basalt (grey black hard)	100'	132'	
Ashstone (very black)	132'	137'	
Shale (dark brown)	137'	148'	
Basalt (hard black) w.b.	148'	150'	70'
Basalt (hard grey black)	150'	163'	70'
Existing well log after 1 hr. before deepening.			

Work started 10/4/75 19 Completed 10/4/75 19

Date well drilling machine moved off of well 10/5/75 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] Pete Tolmasoff Date 10/5, 1975

(Drilling Machine Operator)
Drilling Machine Operator's License No. 320

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name Pete Tolmasoff Well Drilling
(Person, firm or corporation) (Type or print)

Address Turner, Ore.

[Signed] Pete Tolmasoff (Water Well Contractor)

Contractor's License No. 410 Date 10/5/75, 19