· · · · · · · · · · · · · · · · · · ·		Rola - 2	\cap
WATER WELL REPORT STATE OF OREGON MARA BANK FEB 1119	ED State Well No	oskm-o	.)
STATE OF OREGON	OO State Permit No.		
		C	**************************************
WATER RESOURCE	GON LOCATION OF WELL:	-	
		ll number	
Name Dale Jonds	County Marlon Driller's well 4 4 Section 20 T. 8S	R. 2W	W.M.
Address 233 Howell Prairie Rd. S.E.		Subdivision	
City Salem State Oregon	Tax Lot # Lot Blk Address at well location: Ahrens Rd.	GUNULY 101011	······································
(2) TYPE OF WORK (check):	Address at well location: All ens hu. Turner, Ore	gon	-
New Welly Deepening Reconditioning Abandon I If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed v Depth at which water was first found	vell. 12	O ft.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Static level 85 ft. below	land surface. Date 1–	
		per square inch. Date	<u> </u>
Rotary Air XX Driven Domestic Industrial Municipal Rotary Mud Dug Irrigation XX Test Well Other Bored Thermal: Withdrawal Reinjection	(12) WELLLOG: Diameter of well below	w casing	
VY NY	Depth drilled 170 ft. Depth of	of completed well 17	0 ft.
(5) CASING INSTALLED: Steel XX Plastic Threaded Welded XX 6 "Diam. from	Formation: Describe color, texture, grain size and st thickness and nature of each stratum and aquifer per for each change of formation. Report each change ir and indicate principal water-bearing strata.	netrated, with at least o	ter Level
LINER INSTALLED:	MATERIAL	From To	SWL
4 "Diam. from 0 ft. to 170 ft. Gauge 160 PSI PVC	Decomposed Rock	0 3	
	Brown Clay	3 11	
(6) PERFORATIONS: Perforated? XYes D No	Tan Clay	11 18	
Type of perforator used Electric Saw Size of perforations 1/8 in. by 8 in.	Dark Gray Sticky Clay	18 21	<u> </u>
	Gray Shale	21 65	
150 perforations from	Light Gray Shale	65 115	
perforations from	Multi-Colored Sandstone	115 136	
	Light Gray Sandstone	136 157	0
(7) SCREENS: Well screen installed? □ Yes XKNo Manufacturer's Name Model No. Type Model No. Diam. Slot Size Diam. Slot Size Slot Size Set from ft. to ft.	Multi-Colored Sandstone		851
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		•	
Was a pump test made? Yes XNo If yes, by whom?			
gal/min. with ft. drawdown after hrs.			
"Air Test May Fluctuate			
Air test 90 gai./min. with drift stell at 11. Ins.			
Bailer test gal/min. with ft. drawdown after hrs.		-++	
Artesian flow g.p.m.			0.0
Depth artesian flow encountered	Work started 1-26 19 82 Comp		<u>1982</u>
(9) CONSTRUCTION: Special standards: Yes D Not Not Cement	Date well drilling machine moved off of well Drilling Machine Operator's Certification	<u>1-28</u>	1982
Well sealed from land surface to	This well was constructed under my direct and information reported above are true to m [Signed]	wheet knowledge ar	nd helief
Diameter of well bore below seal In. Number of sacks of cement used in well seal	(Drilling Machine Operator)	1195	
Number of sacks of cement used in well sear How was cement grout placed? <u>Air Grout Pump</u>	Drilling Machine Operator's License No		
	Water Well Contractor's Certification: This well was drilled under my jurisdict	tion and this report	is true to
Was pump installed? Yes Type Sub HP 1½ Depth 157 ft Was a drive shoe used? XYes D No Plugs Size: location ft	This well was drilled under in Jurisdiction and this report is the to the best of my knowledge and belief. Name 		
Did any strata contain unusable water? 🛛 Yes XX No	- Address		
Type of Water? depth of strata Method of sealing strata off	[Signed] Dary Mond	tractor)	- 00
Was well gravel packed? Ves XXVo Size of gravel:		1 - 5()	, 19
Gravel placed from ft. to ft.			
NOTICE TO WATER WELL CONTRACTOR	WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310	, S	P*12658-690