The original and fire ope CE VE VATER WELL REPORT filed with the MAY 2 1969 STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310 STATE OF OREGON 97310 Within 30 days from TACLE NGINEER (Please type or print) of well completion SALEM OREGON



State Permit No. .

(1) OWNER:	(11) LOCATION OF WELL:			
Name City Of Aumsville	County Marion Driller's well nu	mber 3	64	
Address Aumsville, Ore.	SE ¼ SW ¼ Section 25 T. 8S			W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	corner		
New Well Deepening Reconditioning Abandon Key by describe material and proceeding by Keyn 12				
If abandonment, describe material and procedure in Item 12.		<u></u>		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of well b	elow casi:	ng 10)
Cable Domestic Industrial Municipal X	Depth drilled 60 ft. Depth of comple	eted well	60) ft.
Dug Bored IIrrigation Test Well X Other	Formation: Describe color, texture, grain size a	and struct	ure of m	aterials;
CASING INSTALLED: Threaded Welded X	and show thickness and nature of each stratus with at least one entry for each change of form			
12 " Diam. from 0 ft. to 52 ft. Gage . 250	in position of Static Water Level as drilling pro			
	MATERIAL	From	То	SWL
ft. Toft. Gage	Top soil	0 '	3 1	
PERFORATIONS: Perforated? Yes No.	Glay (firm-brown)	3 1	5 (
The of perforator used Mills	Clay & cobbles (packed)	51	11'	
	Cement gravel	11 *	201	
	Clay & gravel (packed)	201	25 1	
250 perforations from 31 ft. to 51 ft.	Cement gravel	25'	30 t	10
perforations from ft. to ft.	Silted gravel	301	35	<u> 10'</u>
perforations fromft. toft.	Clay & gravel (packed)	351	40	701
perforations fromft. toft.	Silted gravel (soft)	40 [†]	45° 50°	10'
	Tan clay (soft)	501	601	
(7) SCREENS: Well screen installed? Yes X No	Zan Glay (SOLO)	50	- 00	
Manufacturer's Name		-		
Type Model No.	-			
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.				
Diam. Slot size Set from ft. to ft.				
(8) WATER LEVEL: Completed well.		ļ		
Static level 10 ft. below land surface Date 4/29/69				
ian pressure lbs. per square inch Date				
(9) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? Yes No If yes, by whom?			•	. martina
Yield: gal./min. with ft. drawdown after hrs.	Work started 4/24/69 19 Complete	$\frac{4}{2}$	<u> </u>	19
" " " " " " " " " " " " " " " " " " " "	Date well drilling machine moved off of well 4	/29/6	9	19
" " " "	Drilling Machine Operator's Certification:			
Bailer test 20 gal./min. with 25 ft. drawdown after 1 hrs.	This well was constructed under my di	rect supe	ervision.	Mate-
Artesian flow g.p.m. Date	rials used and information reported above knowledge and belief.	e are tr	ue to n	ny pesi
	1 1 1 4 1 1	Date 4./		
	Drilling Machine Operator	<i>→</i> aoc ∞./		, 10
(10) CONSTRUCTION:	Drilling Machine Operator's License No. 3	20		
Well seal—Material used Bentonite slurry Depth of seal drilled in 30 ft.	Water Well Contractor's Certification:		,	
10	This well was drilled under my jurisdiction and this report			
Diameter of well bore to bottom of seal	true to the best of my knowledge and belief.			
Was a drive shoe used? Yes □ No	NAME Pete Tolmasoff Well Drilling			
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	(Type	or print)	
Type of water? depth of strata	Address Turner, Ore.	***************************************		••••••
	(A V C) D	سد د برر	مراس	
Method of sealing strata off	[Signed] (Water Well Contrac	tor)		
Was well gravel packed? Yes K No Size of gravel:		30/69		10
Gravel placed from ft to ft	Contractor's License No 1410 Date 4/	~ U / n :	7	19