

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

RECEIVED MAY 24 1968

WATER WELL REPORT

STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

REGISTERED ENGINEER SALEM OREGON

(Please type or print) Do not write above this line

State Engineer No. 8/26-25

State Permit No.

App 6 10726 Humsville Min

(1) OWNER:

Name REX LUGAS Address 406 S Hambeck Acumsville

(2) TYPE OF WORK (check):

New Well [checked] Deepening [ ] Reconditioning [ ] Abandon [ ]

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [ ] Driven [ ] Cable [checked] Jetted [ ] Dug [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [ ] Industrial [ ] Municipal [checked] Irrigation [ ] Test Well [ ] Other [ ]

CASING INSTALLED:

10" Diam. from 1 ft. to 170 ft. Gage 2250

PERFORATIONS:

Perforated? [ ] Yes [checked] No.

Type of perforator used

Size of perforations in. by in. perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [ ] Yes [checked] No

Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 1 ft. below land surface Date 4-19-68

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [checked] Yes [ ] No If yes, by whom? Miller & West Yield: 280 gal./min. with 260 ft. drawdown after 8 hrs.

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m. Date

Temperature of water Was a chemical analysis made? [ ] Yes [checked] No

(10) CONSTRUCTION:

Well seal—Material used Bentonite Depth of seal 25 ft. Diameter of well bore to bottom of seal 15 in. Were any loose strata cemented off? [ ] Yes [checked] No Depth Was a drive shoe used? [checked] Yes [ ] No Did any strata contain unusable water? [ ] Yes [checked] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [ ] Yes [checked] No Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Marion Driller's well number 1/4 Section N. 525 T. 8, S. R. 2, W.M. Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 10

Depth drilled 330 ft. Depth of completed well 330 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include: BROWN - CLAY 0-38, COARSE GRAVEL 38-89, BLUE - CLAY 89-145, BROWN + RED - Completely decomposed rock with thin layers of boulders or broken rock 145-165, WHITE + GRAY - CLAY 165-195, BLACK - 195-197, BROWN - BROKEN ROCK 197-280, WHITE - CLAY STONE 280-282, BROWN - BROKEN AREA 282-285, WHITE SANDY - CLAY STONE 285-320, BLUE - 320-330

Work started 4-1 1968 Completed 4-19 - 1968

Date well drilling machine moved off of well 4-19 - 1968

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Miller & West Date 4-24, 1968 (Drilling Machine Operator)

Drilling Machine Operator's License No. 188

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Miller - Robinson & West (Person, firm or corporation) (Type or print)

Address 5545 Joseph St. S.E. Salem

[Signed] Harold R. Miller (Water Well Contractor)

Contractor's License No. 37 Date 4-24, 1968