NOTICE TO WATER WELL CONT:

The original and first copy
of this report are to be

JAN 28 1983 TER WELL REPORT

State Permit No.

filed with the		ENGINEER	OF OREGO
STATE ENGINEER, SALEM 10 within 30 days from the	OFFICIAL	CINCIPLE	type or print)
within 30 days from the of well completion.	date	A OREGON	
or well completed.	- SALED	A. CANADAN	

State	Well	No.	4/2W-	- 7	H
-------	------	-----	-------	-----	---

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level
Name Milo Schneider	Was a pump test made? Types I No If yes, by whom? Milo Schne Yield: 800 gal./min. with 92 ft. drawdown after 1 hrs.
Address Star Rt., Box 97	Yield: 800 gal./min. with 92 ft. drawdown after 1 hrs. 700 " 78 " 82 "
St. Paul, Oregon	
(2) LOCATION OF WELL:	500
County Marion Driller's well number	
34 34 Section 7 & ST.4S R.2W	W.M. Artesian flow g.p.m. Date W.M. Temperature of water 55 Was a chemical analysis made? Yes 1 No
Bearing and distance from section or subdivision corner	Temperature of water 55 was a chemical analysis made? [] Yes [] No
8.19 Ch N. 34° - 47° W. of N.E. Cor	(12) WELL LOG: Diameter of well below casing 153
C1 #97 Township 4S R 2W Sec 7 & 8	Depth drilled 156 ft. Depth of completed well ft.
	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
	MATERIAL FROM TO
(3) TYPE OF WORK (check):	0 to 2 top soil 0 2
	ndon D brown clay 2 19
If donment, describe material and procedure in Item 12.	brown clay w/ sand layers 19 62
(A) PROPOSED TICH (I I) (E) MITTEL OF I	blue clay few sand layers 62 104
(4) PROPOSED USE (check): (5) TYPE OF W	hard blue clay 104 125
Domestic Industrial Municipal Cable Jette	sand & wood 125 126
Irrigation ☐ Test Well ☐ Other ☐ Dug ☐ Bore	ed sand & rayers prown cray rec
	brownish yellow clay 156
(6) CASING INSTALLED: Threaded Welded X	
Diam. from OC 156	50
B ft. to ft. Gage	
"Diam. from ft. to ft. Gage	manufacture for the second sec
(7) PERFORATIONS: Perforated? ☑ Yes ☐ N	Vo.
	Pump was set 146, overall
10	Air line 130' with direct reading gau
Size of perforations 4 in. by 10 in. 320 ea perforations from 96 ft to 156	gt
perforations from ft. to	61
perforations from ft. to	
perforations from ft. to	##
perforations from ft. to	
periorations from	anna do
(8) SCREENS: Well screen installed Yes X N	No
Manufacturer's Name	
Model No.	
Slot size Set from ft. to	ft. Work started 3-10-629 . Completed 12-29-62 19
Diam. Slct size Set fromft. to	
(9) CONSTRUCTION:	(13) PUMP:
Well seal—Material used in seal	Manufacturer's Name Layne & Bowler
Depth of seal 13 ft, Was a packer used? N	O turbine H.P. 20
Diameter of well bore to bottom of sealin.	Window Will Continuationly Continue
Were any loose strata cemented off? Tyes No Depth	
Was a drive shoe used? Tyes 🖾 No =	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was well gravel packed? A Yes I No Size of gravel: 3/4	.r.v.yas
Gravel placed from 13 ff to 156 ft.	NAME Milo Schneider
Did any strata contain unusable water? ☐ Yes 💆 No	(Person, firm or corporation) (Type or print)
Type of water? Denth of strata	Address Star Rt., Box 97, St. Paul
Method of sealing strate off	Drilling Machine Operatory Livense No. 212
	Drilling Machine Operator's License No. 212
(10) WATER LEVELS:	5 69 [Signed] Mila Schneider
Static level 14 ft. below land surface Date 4-1	(Water Well Contractor)
Artesian pressure lbs. per square inch Date	Contractor's License No. 387 Date 12-29 , 19 62