

DESTROYED

owner given Appl. form etc,
7/13/60 wsb,

G(11)

File Original and First Copy with the STATE ENGINEER, SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON

State Well No. 4/2W-8.B

State Permit No. G-1651

MART. 11/18

G-1806

(1) OWNER:

Name Nelson Tribbett
Address Newberg, Oregon

(2) LOCATION OF WELL:

County MARION Owner's number, if any- #2
NW 1/4 NE 1/4 Section 8 T. 4S R. 2W W.M.
Bearing and distance from section or subdivision corner
2000 feet South & 1500 feet west from NE Cor.
Section 8, T4S, R2W

(3) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 11.

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(6) CASING INSTALLED:

Threaded Welded
12" Diam. from 0 ft. to 140 ft. Gage
8" Diam. from 0 ft. to 227 ft. Gage
8" Diam. from 0 ft. to 84 ft. Gage

(7) PERFORATIONS:

Perforated? Yes No
Type of perforator used Millknife
SIZE of perforations 1/4 in. by 2 in.
40 perforations from 145 ft. to 150 ft.
36 perforations from 84 ft. to 88'6" ft.
40 perforations from 55 ft. to 60 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(8) SCREENS:

Well screen installed Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

CONSTRUCTION:

Was well gravel packed? Yes No Size of gravel: 1/4 inch
Gravel placed from 0 ft. to 86 ft.
Was a surface seal provided? Yes No To what depth? 66 ft.
Material used in seal-
Did any strata contain unusable water? Yes No
Type of water? Depth of strata
Method of sealing strata off

(10) WATER LEVELS:

Static level 27 ft. below land surface Date
Artesian pressure lbs. per square inch Date
Log Accepted by: Tribbett & Son
[Signed] Nelson L. Tribbett April 5, 1960
(Owner)

(11) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom? - Driller
Yield: 200 gal./min. with 127 ft. drawdown after 8 hrs.
" " " "
" " " "
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water 52° Was a chemical analysis made? Yes No

(12) WELL LOG:

Diameter of well 12 inches.
Depth drilled 242 ft. Depth of completed well 242 ft.
Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.

MATERIAL	FROM	TO
Surface	0	3
Sandy brown clay	3	16
Gray sandy clay	16	26
Blue sandy clay	26	45
Sand	45	88
Blue sandy clay	88	90
Gray green clay	90	107
Dry sand and clay	107	113
Broken sand and clay	113	140
Coarse sand and small gravel	140	155
Blue clay	155	165
Blue clay	165	170
Gray sandy clay	170	180
Tough gray clay	180	188
Brown and white clay	188	194
Sandy blue clay	194	198
Brown clay	198	205
Blue clay	205	227
Sand	227	241
Blue clay	241	242

(7-29-70) WELL DESTROYED
NEW WELL NEAR BY

Work started Feb. 10 1960. Completed April 5 19 60

(13) PUMP:

Manufacturer's Name
Type: Turbine H.P. 15

Well Driller's Statement:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME John Truman Miller
(Person, firm, or corporation) (Type or print)

Address P. O. Box 42 Hubbard, Oregon

Driller's well number

[Signed] John Truman Miller
(Well Driller)

License No. 177 Date April 5, 19 60