NOTICE TO WATER WELL CONTRACTOR

The original and first copy SEP 4 196WAFER WELL REPORT

of this report are to be
filed with the

STATE ENGINEER, SALEM 10, OREGON E

within 30 days from the date
of well completion.

STATE OF OREGON

(1) OWNER OF THE OF OREGON

(1) OWNER OF THE OF OREGON

(1) OWNER OF THE OF OREGON

State Well No.

State Permit No. .

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level Drail low
Name Nelson Tribbett & Son	Was a pump test made? Yes No If yes, by whom? Driller
Address Star Rt., Box 96	Yield: 400 gal./min. with 66 ft. drawdown after 8 - hrs.
St. Paul, Oregon	" " " "
(2) LOCATION OF WELL:	" " "
County Marion Driller's well number	Bailer test gal./min. with ft. drawdown after hrs.
NW 14 NE 14 Section 8 T. 4S R. 2W W.M.	Artesian flow g.p.m. Date
Bearing and distance from section or subdivision corner	Temperature of water 52 Was a chemical analysis made? ☐ Yes ♣ No
2000 feet South - 1500 feet West from	(12) WELL LOG: Diameter of well below casing
NE Cor. Section 8, T4S, R2W	Depth drilled
K.	10. Septil of completed well 1/1 It.
	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
	MATERIAL FROM TO
(3) TYPE OF WORK (check):	Pulled 140° of 12 " casing
Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	Pulled 84: of 8" casing
a Jandonment, describe material and procedure in Item 12.	Pulled 84' of 2" pipe
(4) PROPOSED USE (check): (5) TYPE OF WELL:	was in the 8"
Domestic   Industrial   Municipal   Rotary   Driven	
Cable  Jetted	Note: the 12" was around the
Trigation 1 Test wen   Other   Dug   Bored	8" that is left
(6) CASING INSTALLED: Threaded □ Welded □	the 84° of 8" was on the outside
"Diam. from None ft. toft. Gage	of the 12" the 2" was inside of the above
" Diam, fromft, toft. Gage	
"Diam. fromft. Gage	8" and full of gravel
(7) PERFORATIONS: Perforated? 🛪 Yes 🗆 No	Installed 2 feed pipes 5" x 118"
(7) PERFORATIONS: Perforated? X Yes No Type of perforator used Mills Knife	and 5" x 222"
Size of perforations 3/8 X 2n. by in.	to top of concrete
120 perforations from 150 ft. to 160 ft.	
400 perforations from 120 ft. to 145 ft.	
perforations from ft. to ft.	
perforations from ft. to ft.	
perforations from ft, to ft.	
(8) SCREENS: Well screen installed ☐ Yes X No	
Manufacturer's Name	
Model No.	
Diam Slot size Set from ft. to ft.	Work started 19 . Completed 8-1-62 19
Diam. Slot size Set from ft. to ft.	Date well drilling machine moved off of well 8-1-62 19
(9) CONSTRUCTION:	(13) PUMP:
Well seal—Material used in sealCONCRETE	Manufacturer's Name Layne & Bowler
Depth of seal 10 ft. Was a packer used?	Type: setuis7pe overall H.P. 30
Diameter of well bore to bottom of seal . I feet in.	airline 140°
Were any loose strata cemented off? Tyes No Depth	Water Well Contractor's Certification:
Was a drive shoe used? ★□ Yes □ No Šize of gravel:3/4	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Gravel placed from 10 t ft to 160 t ft.	NIABETT RESIDENCE STATE OF THE
Did any strata contain unusable water? Yes No	NAME Milo Schneider  (Person, firm or corporation) (Type or print)
Type of water? Depth of strata	Address Star Rt., Box 97 St. Paul, Orego
Method of sealing strata off	
(10) WATER LEVELS:	Drilling Machine Operator's License No. 212
Static level 24 ft. below land surface Date 7-30-62	[Signed] The Schneider
Artesian pressure lbs. per square inch Date	(Water Well Contractor)
The state of the s	Contractor's License No. 387 Date 3-120 1062

(USE ADDITIONAL SHEETS IF NECESSARY)