NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED DEC 24 1965 STATE ENGINEER SALEM, OREGON

G 3485 MAR 1.132

RECEIVED JAN 3 1966 STATE ENGINEER

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

State Well No. 4/2w-9A

State Permit No.

(1) OWNER:

Name: Amiel Desmet

Address: Rt. 1, Box 110, Aurora, Oregon

(2) LOCATION OF WELL:

County: Marion Driller's well number

¼ ¼ Section 9 T. 4S R. 2W W.M.

Bearing and distance from section or subdivision corner

(3) TYPE OF WORK (check):

New Well [X] Deepening [ ] Reconditioning [ ] Abandon [ ]

If abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):

Domestic [ ] Industrial [ ] Municipal [ ]
Irrigation [X] Test Well [ ] Other [ ]

(5) TYPE OF WELL:

Rotary [ ] Driven [ ]
Cable [X] Jetted [ ]
Dug [ ] Bored [ ]

(6) CASING INSTALLED: Threaded [ ] Welded [X]

18" Diam. from 0 ft. to 39 ft. Gage 250
12" Diam. from 0 ft. to 113 ft. Gage
" Diam. from ft. to ft. Gage

(7) PERFORATIONS: Perforated? [X] Yes [ ] No

Type of perforator used: torch

Size of perforations 3/8 in. by 8 in.

360 perforations from 82 ft. to 112 ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(8) SCREENS: Well screen installed? [ ] Yes [X] No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(9) CONSTRUCTION:

Well seal—Material used in seal: Bentonite

Depth of seal 39' ft. Was a packer used? yes

Diameter of well bore to bottom of seal 24 in.

Were any loose strata cemented off? [ ] Yes [X] No Depth

Was a drive shoe used? [ ] Yes [X] No

Was well gravel packed? [X] Yes [ ] No Size of gravel: 3/8 - 3/4

Gravel placed from 0 ft. to 112 ft.

Did any strata contain unusuable water? [ ] Yes [X] No

Type of water? depth of strata

Method of sealing strata off

(10) WATER LEVELS:

Static level 9 ft. below land surface Date

Artesian pressure lbs. per square inch Date

(11) WELL TESTS: Drawdown is amount water level is lowered below static level

Was a pump test made? [ ] Yes [X] No If yes, by whom?

Yield: 500 gal./min. with 38 ft. drawdown after 6 hrs.
" with air lift " "
" " " "

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m. Date

Temperature of water 54 Was a chemical analysis made? [ ] Yes [X] No

(12) WELL LOG: Diameter of well below casing 0

Depth drilled 113 ft. Depth of completed well 113 ft.

Formation: *Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.*

MATERIAL	FROM	TO
Blue clay	5	39½
Blue sand	39½	65
Blue clay	65	74
Blue sand small layer clay	74	112
Clay	112	113

Work started 5-17-65 19 . Completed 6-25 1965

Date well drilling machine moved off of well 19

(13) PUMP:

Manufacturer's Name: none

Type: H.P.

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Milo Schneider (Person, firm or corporation) (Type or print)

Address Star Rt., Box 97, St. Paul, Oregon

Drilling Machine Operator's License No. 212

[Signed] Milo Schneider (Water Well Contractor)

Contractor's License No. 387 Date 12-15-65, 19

(USE ADDITIONAL SHEETS IF NECESSARY)