WATER WELL REPORT STATE OF OREGON

WATER RESOURCES DEPT. SALEM, OREGON



State Well No. tate Permit No.

(1) OWNER:	(10) LOCATION OF WELL:	==
Name Gary Benson	County Marion Driller's well number	
Address 31431 Elderberry Dr. S	4 4 Section 6 T. 8S R.	<u>3W</u> W.M.
City Salem State OREGON	Tax Lot # Lot Blk	Subdivision
(2) TYPE OF WORK (check): Address at well location: Salem Driving Range		
New Well Deepening □ Reconditioning □ Abandon □		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well	l.
	Depth at which water was first found 33	ft.
(3) TYPE OF WELL: (4) PROPOSED USE (check):		surface. Dat 9/17/85
Rotary Air Driven Domestic 💢 Industrial Dunicipal D	Artesian pressure lbs. per square inch. Date	
Potary Mudgang Dug Irrigation Test Well Other Bored Thermal: Withdrawal Reinjection	(12) WELL LOG: Diameter of well below cas:	811
	Depth drilled 100 pt. Depth of completed well 100 ft.	
(5) CASING INSTALLED: Steel Threaded Plastic Welded X	Formation: Describe color, texture, grain size and structure of materials; and show	
	thickness and nature of each stratum and aquifer penetrat	ted, with at least one entry
"Diam. from	for each change of formation. Report each change in posi and indicate principal water-bearing strata.	tion of Static Water Level
LINER INSTALLED:	MATERIAL	From To SWL
_		
	- clay brown	0 13
(6) PERFORATIONS: Perforated? ▼ Yes □ No		70 70
Type of perforator used mills	clay blue	13 16
Size of perforations $3/8$ in. by $2/8$ in.	al ment and granter	16 33
	claystone grary	10 35
perforations from ft. to ft.	claystone broken	33 40 11
perforations from ft. to ft.	C.Lay 400116 OI ORSII	<u> سد سه رو</u>
(7) SCREENS: Well screen installed? ☐ Yes XX No	claystone hard slightly	
Manufacturer's Name	, -	40 75 77
Type Model No	Tractured	40 13 12
Diam.	claystone hard soft layers	75 100 11
<u>Diam.</u> Slot Size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Sciow Statute level		
a pump test made? Yes X No If yes, by whom?		
d: gal/min. with ft. drawdown after hrs.		
Air test gal./min. with drill stem at ft. hrs.		
Bailer test 20-23 gal/min. with 79 ft. drawdown after 2 hrs.		
sian flow g.p.m.		
Depth artesian flow encountered ft.	Work started 9/10/85 19 Completed	9/21/85 19
(9) CONSTRUCTION: Special standards: Yes □ No XX	Date well drilling machine moved off of well 9/25/85 19	
Well seal—Material used cement grout	Drilling Machine Operator's Certification:	
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.	
Diameter of well bore to bottom of seal		
Diameter of well bore below seal 8 in.	[Signed] Date 9/30/859 Date 9/30/859	
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No921	
How was cement grout placed?pumped		
	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
Was pump installed?	1	
Was a drive shoe used? X□ Yes □ No Plugs Size: location ft. Did any strata contain unusable water? □ Yes □ Yes	Name Robinson. Well. Drilling. (Type or print)	
Type of Water? depth of strata	Address 4520 Selem Dallag Hwy Salen	
Method of sealing strata off	[Signed] George Rehizon	
	(Water Well Contractor)	, ,
#MAX	Contractor's License No13Date 9/4/30/85	, 19
Gravel placed from ft. to ft.		