ORIGINAL File Original, and	WATER WELL DRIL	LERS REPORT Do Not State Well No. 8/2w - 15/19	
Duplicate with the STATE ENGINEER, SALEM, OREGON			
(1) OWNER: Wilh		(10) WELL TESTS:	
Address P.O. Box 647 Salem (2) LOCATION OF WELL: Elev. 465		Was a pump test made? Yes No If yes, by whom? The Notes Co.	
		Yield: 2.0 gal./min. with 9.5 ft. draw down after / hrs.	
		29 21 29 29	
		Artesian flow g.p.m.	
D D D - CO. 127 1/1/1		Shut-in pressure lbs. per square inch.	
Bearing and distance from section or subdivisi	4116	Bailer test g.p.m. with ft. drawdown	
44 c. L. E. X. / 2 . 1 M. / / 2 . 1	on corner	Temperature of water Was a chemical analysis made? ☐ Yes ☐ No	
Lot#1 in LoneHell Fruit Troits		Was electric log made of well?	
		(11) WELL LOG:	
/ TYPE OF WORK (check):		Diameter of well, inches.	
ew well Deepening Reconditioning Abandon		Total depth 91 ft. Depth of completed well 91 ft.	
If abandonment, describe material and procedure in Item 11.		Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated with at least one entry faces by	
(4) PROPOSED USE (check): (5) EQUIPMENT:		stratum penetrated, with at least one entry for each change of formation. Off. to ft.	
mestic Industrial Municipal [Rotary 🗆	1 " a) " Plot.	
	Cable	to reasture	
	□ Dug Well □	20 56 Com	
(6) CASING INSTALLED:	If gravel packed	36 70 Hard Busalt	
Threaded Welded	n graver packed	70 76 " Soft Coarse Basalt	
Gage		76 79 Fine Busalt	
FROM Oft. to SL ft. Diam. P Wall	Diameter from to of Bore ft. ft.	74 F3 Sett Course Baset	
27 y 27 29 29	27 27	83"85" 4 Fine n	
39 39 39 39	" "	15 84 Hard	
27 27 28 29 29	,, ,,	86 "95" Basalt	
33 31 37 37 27	. 27 22	95"91 " Seft Coarse Basult	
32 32 33 33 31	<u>"</u> "	+ 98" 91/2 " Herd Becalt.	
Type and size of shoe or well ring	Size of gravel:	11 11	
Describe joint))	
(7) DEDEODATIONS.		" "	
(7) PERFORATIONS:		2)	
Type of perforator used	and the second s	11 11	
	length, by in.	11 11	
OM ft. to ft. perf	f per foot No. of rows	n n	
		n n	
	>> 19	"	
	""""	11 11	
	"""	" "	
SCREENS:		33	
Give Manufacturer's Name, Model No. and Size		11 2)	
		1) 1)	
(8) CONSTRUCTION:		1) 1)	
Was a surface sanitary seal provided? ☐ Yes ☐	No To what depth ft.	11 11	
Were any strata sealed against pollution?	es No	Ground elevation at well site feet above mean sea level.	
If yes, note depth of strata		Work started	
FROM / ft. to	ft.	900 20 1000 completed 3374 1856	
27 - 29	,,	Well Driller's Statement:	
METHOD OF SEALING		This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
(9) WATER LEVELS:		NAME A	
Depth at which water was first found	257 ft.	(Person, firm, or carrioration) (Typed or printed)	
Standing level before perforating		Address "	
	_1/2//	 // // 	
Standing level after perforating 24,49	-6-12-62 ft.	Driller's well pumber	
Log Accepted by:		[Signed]	
[Signed] John Word than Dated	19	(Well Driller)	
by Wim Dayle	,	License No Dated, 19	

: