NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 9/310
within 30 days from the date
of well completion.

Rev

RECEIVED
WATER WELL REPORT
STATE OF OREGON OCT 2 3 1974 State Well No. 4

ate Permit No. ..

(Please type or print	SIAIE	ENGINEER	Sta
(Do not write above this	BALEM.	OREGON	

(1) OWNER:	(10) LOCATION OF WELL:
Name St. Paul Cemetery Association	County Marion Driller's well number 7411
Address St. Paul. Ore. 97137	1/4 1/4 Section 19 T. 4S R. 2W W.M.
Address Dos Lettals	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well 🕱 Deepening 🗌 Reconditioning 🗍 Abandon 🗍	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 61 ft.
Rotary Driven Domestic Industrial Municipal	Static level 56 ft. below land surface. Date 9_17_74
Cable	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded 10 Diam. from 1'3" ft. to 236 ft. Gage 250 6 Diam. from ft. to 58 ft. Gage 250 Threaded 10 Threaded 10	(12) WELL LOG: Diameter of well below casing Depth drilled 243 ft. Depth of completed well 236 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used cutting torch	MATERIAL From To SWL
- 10	See sheet attached
Size of perforations 3/8 in. by 0 in. 200 perforations from 136 ft. to 156 ft.	
200 perforations from 196 ft. to 216 ft.	7
perforations from	
perforations fromft. toft	
(7) SCREENS: Well screen installed? Yes Y No	
Manufacturer's Name	
TypeModel No,	7
Diam. Slot size Set from ft. to ft.	H
Diam Slot size Set from ft. to ft.	
Drawdown is amount water level is	
lowered below static level	
Was a pump test made? XXYes \(\subseteq No \) If yes, by whom? driller	Part Comment of the C
d: 710 gal./min. with 44 ft. drawdown after 7 hrs.	
435 " 27 " 8 "	
" " "	y and Miller Cale
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered	Work started 8-21 1974 Completed 10-16 1974
	Date well drilling machine moved off of well 10-16 19 71
(9) CONSTRUCTION: pressure grouted Well seel Material used cement and zonolite	Drilling Machine Operator's Certification:
Well Seal-Material about	This well was constructed under my direct supervision.
Well sealed from land surface to ft.	Materials used and information reported above are true to my best knowledge and belief
Diameter of well bore to bottom of salin. Diameter of well bore below sealin.	
Diameter of well bore below seal	(Drilling Machine Operator)
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No
Number of sacks of petitoritie used in	
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons 1 bs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	
Did any strata contain unusable water? I Yes A No	Name Milo Schneider Equipment Co. (Person, firm or corporation) (Type or print)
atrata	Address Star Rt., Box 977 St. Paul Ore
The state of the s	Mila La Marie Voc
Method of sealing strata off Was well gravel packed? M Yes I N Size of gravel:	[Signed] (Water Well Contractor)
hattom	Contractor's License No. 387. Date 10-17. 19.74
Gravel placed from ft. to ft.	Community of the state of the s

KEULIVEL

OCT231974 STATE ENGINEER 7411 SALEM, OREGON

	St.	Paul	Cemetery
-75	: N .	アとしょ	Centereary

Material	From	To
Top soil	0	3
Brown clay Brown silty clay Brown soft clay Brown clay Blue clay Fine blade sand	0 3 19 34 46 48 61	19 34 46 48 61 75
Cemented black sand Gray clay Gray sandy clay (dry) Gray clay Gray sandy clay (Wood 118)	75 81 89 100)104	81 89 100 104 119
Black sand & gravel (1½") Black sand Black sand & gravel (2½") Gray clay Black gravel Blue green clay	127	131 145 180 181 196
Black sand (Wood 205) Brown sandy clay Fea gravel Brown sandy clay Gray clay	196 206 211 _ 214 219	206 211 214 219 243