NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

RECEIVED
JAN 4 1979
WATER RESOURCES DEPT.
SALEM, OREGON

MARION

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

12650

State Well No. 8S/3W-27bc
State Permit No.

(1) OWNER:
Name Harvey Rosse
Address 1040 Southridge Place
Salem, Ore.

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED: Threaded ☐ Welded ☒
6" Diam. from 0 ft. to 112 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS: Perforated? ☐ Yes ☒ No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " "
" " "
~~Bailer~~ Air test 30 gal./min. with Stem at 264 ft. drawdown after 1½ hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 7 sacks
How was cement grout placed? Poured.

Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Marion Driller's well number 665-78
SW ¼ NW ¼ Section 27 T. 8S R. 3W. W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 240 ft.
Static level 170 ft. below land surface. Date Dec. 14, 1978
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6
Depth drilled 265 ft. Depth of completed well 265 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Soil	0	3	
Sand, Clay, Brown	3	25	
Clay, Red	25	97	
Decomposed Rock	97	104	
Rock, Med Hard	104	138	
Rock, Black, Hard	138	240	
Rock, Black-Brown-Gray	240	265	170.

Work started Nov. 28 1978 Completed Dec. 14 1978
Date well drilling machine moved off of well Dec. 14 1978

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] William C. Perry Date Dec. 14, 1978
(Drilling Machine Operator)
Drilling Machine Operator's License No. 117

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Long Drilling (Person, firm, or corporation) (Type or print)
Address 11401 Stayton Rd. SE, Aumsville, Ore.
[Signed] William C. Perry (Water Well Contractor)
Contractor's License No. 75 Date Dec. 14, 1978

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119