AUG 3 1973 State Well No. 48/2W-34 NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

(Do not write above this line) TE ENGINGATE Permit No. ...

	(10) LOCATION OF WELL:
1) OWNER:	County Marion, Driller's well number 7305
	1/4 1/4 Section 24 T. 45 R. 2W W.M.
Mondleusn, Ore 97071	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	Bearing and distance from section of subdivision control
A1	
New Well A Deepening Reconditioning Abandon Abandon Carlo Reconditioning Abandon Carlo Reconditioning Carlo Reco	MARKED I DIVIN Completed well
	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 15 ft.
Rotary Driven Domestis Dindustrial Municipal Domestis	Static level 45 ft. below land surface. Date 7-11-73
Dug Bored I Irrigation F Test Well Other	Artesian pressure Libs. per square inch. Date
(5) CASING INSTALLED: Threaded \(\) Welded \(\) \(\) Gage \(\) 250 \(\) " Diam. from \(\) ft. to \(\) ft. Gage \(\) Threaded \(\) (A graph of the condition of the cond	(12) WELL LOG: Diameter of well below casing Depth drilled /3/ ft. Depth of completed well 131'6" ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used Milly Enife	MATERIAL From To SWL
Size of perforations 5/14 in. by 2 in.	Top soil, 04
560 perforations from 101 ft. to 116 ft.	Irown Class 4 15
perforations from	Sympset clay 15 30
	drawn class 30 62
perforations from ft. to ft.	angele 1 62 78
(7) SCREENS: Well screen installed? Yes No	My 1 13
Manufacturer's Name	black Sand & some great 113 115
Type Model No.	gray () 21 / 15 /3/
Diam. Slot size Set from ft. to ft.	
Diam Slot, size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? Yes The No If yes, by whom?	
y : 460- gal./min. with 35 ft. drawdown after 6 hrs.	N. 1. 1. 1. 1. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2.
" " "	
" " "	
	The state of the s
The state of the s	
A sian flow g.p.m.	Work started 12-27 1972 Completed 7-11 1973
perature of water Depth artesian flow encountered ft.	
(9) CONSTRUCTION:	Date well drilling machine moved off of well 4-34 1975
Well seal—Material used Percent summer and Well sealed from land surface to 34 ft. Diameter of well bore to bottom of seal in. Diameter of well bore below seal in.	Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and balief. [Signed]
Number of sacks of cement used in well seal 47 sacks	(Drilling Machine Operator)
Number of sacks of bentonite used in well seal	Drilling Machine Operator's License No
Brand name of bentonite	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? ☐ Yes No Plugs Size: location ft.	Name Mila Schneider Equipment Co.
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)
	Address Star Rt BOX 97 St Paul Ore 9715
2,000	Mil Wille
Method of sealing strata off	[Signed]/. Ula
Was well gravel packed? Yes No Size of gravel:	
Gravel placed from	Contractor's License No. 387 Date 8-1 , 19.75