NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310
within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED
MAR 17 1977
WATER RESOURCES DEPT.
SALEM, OREGON

State Well No. 8S/3W 31bb
State Permit No.

(1) OWNER:
Name Dave McBratney
Address 220 Owens S.
Salem, Oregon 97300

(2) TYPE OF WORK (check):
New Well [X] Deepening [ ] Reconditioning [ ] Abandon [ ]
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary [ ] Driven [ ]
Cable [X] Jetted [ ]
Dug [ ] Bored [ ]

(4) PROPOSED USE (check):
Domestic [X] Industrial [ ] Municipal [ ]
Irrigation [ ] Test Well [ ] Other [ ]

(5) CASING INSTALLED: Threaded [ ] Welded [X]
6" Diam. from 0 ft. to 50 ft. Gage .250
4PVC" Diam. from 0 ft. to 140 ft. Gage .276
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? [X] Yes [ ] No.
Type of perforator used Saw Cut
Size of perforations 3/16 in. by 10 in.
100 perforations from 80 ft. to 140 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? [ ] Yes [X] No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? [ ] Yes [X] No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 15 gal./min. with 75 ft. drawdown after hrs.
AIR
Artesian flow g.p.m.
Temperature of water 51 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement
Well sealed from land surface to 25 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 8 sacks
How was cement grout placed? hand mixed and hand placed
Was a drive shoe used? [X] Yes [ ] No Plugs Size: location ft.
Did any strata contain unusable water? [ ] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [ ] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Marion Driller's well number 25377G
NW ¼ NW ¼ Section 31 T. 8S R. 3W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 80 ft.
Static level 50 ft. below land surface. Date 3/9/77
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6
Depth drilled 140 ft. Depth of completed well 140 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. **Report each change in position of Static Water Level and indicate principal water-bearing strata.**

MATERIAL	From	To	SWL
Top Soil	0	3	
Redish Brown Clay	3	15	
Brown Sandy Claystone	15	63	50
Brown Sandstone	63	75	
Blue Rock	75	84	
Brown Sandrock	84	97	
Fractured Basalt	97	140	

Work started 3/9/77 19 Completed 3/9 19 77
Date well drilling machine moved off of well 3/9 19 77

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] George M. Simpson Date 3/14, 1977
(Drilling Machine Operator)
Drilling Machine Operator's License No. 1072

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Schoen's Electric & Pump
(Person, firm or corporation) (Type or print)
Address 626 W. Queen Albany, Oregon 97321
[Signed] Larry E. Schoen
(Water Well Contractor)
Contractor's License No. 513 Date 3/16, 1977

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119