CLARK & GROFF ENGINEERS INC.
3276 COMM. S.E. SALEM. ORE

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON, within 30 days from the date of well completion.

RECEIVED JUL 29 1968 STATE ENGINEER SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

State Well No. 8/4W-1
State Permit No. 13075

(1) OWNER:
Name ILLAHEE COUNTRY CLUB.
Address SOUTH RIVER ROAD SALEM. ORE

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

CASING INSTALLED:
Threaded ☐ Welded ☒
12" Diam. from 0 ft. to 40' ft. Gage 3/4
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:
Perforated? ☒ Yes ☐ No.
Type of perforator used MILLS
Size of perforations 3/8 in. by 2 1/2" in.
144 perforations from 32' ft. to 36' ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☐ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.
Static level 25' ft. below land surface Date 6-22-68
Artesian pressure lbs. per square inch Date

(9) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☒ Yes ☐ No If yes, by whom? STETTLER SUPPLY
Yield: 235 gal./min. with 20 ft. drawdown after 2 hrs.
" " "
" " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water 52° Was a chemical analysis made? ☐ Yes ☒ No

(10) CONSTRUCTION:
Well seal—Material used BENTONITE
Depth of seal 28' ft.
Diameter of well bore to bottom of seal 16" in.
Were any loose strata cemented off? ☐ Yes ☒ No Depth
Was a drive shoe used? ☒ Yes ☐ No
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(11) LOCATION OF WELL:
County MARION Driller's well number
¼ ¼ Section 1 T. 8S R. 4W W.M.
Bearing and distance from section or subdivision corner

(12) WELL LOG:
Diameter of well below casing 12"
Depth drilled 45' ft. Depth of completed well 45' ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

MATERIAL	From	To	SWL
TOPSOIL	0	2	
CLAY SANDY	2	9	
CONGLOMERATE	9	33	
GRAVEL COARSE	33	36	25'
CLAYSTONE	36	45	

Work started 6-21- 1968 Completed 6-27- 1968
Date well drilling machine moved off of well 6-27- 1968

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] R.F. Sneed Date 6-27, 1968
(Drilling Machine Operator)
Drilling Machine Operator's License No. 187

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
NAME S.A. SNEED & SONS
(Person, firm or corporation) (Type or print)
Address 3910 SILVERTON RD. SALEM. ORE
[Signed] R.F. Sneed
(Water Well Contractor)
Contractor's License No. 6 Date 6-27, 1968

(USE ADDITIONAL SHEETS IF NECESSARY)