NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be JUN 2 1 197 STATE OF OREGON

STATE ENGINEER, SALEM, OF TON THE ENGINEER, SALEM, OF TON THE ENGINEER SALEM. OF TO THE OWNER OF WELL COMPLETED IN COMPLETED TO THE SALEM. OF TON THE SALEM. OF THE OWNER SALEM. OF THE OWNER SALEM.

		9/IW	21	2	_
State	Well No.	1/100		- (<u>).</u>	_
State	Permit N	o. ·		··········	

	(10) LOCATION OF WELL:			
(1) OWNER:	The set one of the second second second			
Name DORSEY GRAY	The state of the s	W.M.		
Address Rt. 1 Box 132	And American / 1/2	#77 T-12		
AUMISVILLE, OREGON	Bearing and distance from section or subdivision corner			
(2) TYPE OF WORK (check):		₹.		
New Well 🖟 Deepening 🗌 Reconditioning 🗍 Abandon 🗍				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	ft.		
(6)	Static level 5 ft. below land surface. Date 5/3	1/		
Cable	Artesian pressure lbs. per square inch. Date			
Dug Bored I Irrigation A lest wen United				
CASING INSTALLED: Threaded □ Welded ☑	(12) WELL LOG: Diameter of well below casing	2		
12 "Diam from 0 ft. to 30 ft. Gage . 250	Depth drilled 30 ft. Depth of completed well 30	£t.		
"Diam. from ft. to ft. Gage	The Pagerine color texture grain size and structure of materials;			
ft. to ft. Gage	and noting of each strainin and addited penetration			
	with at least one entry for each change of formation. Report each c position of Static Water Level and indicate principal water-bearin	g strata.		
PERFORATIONS: Perforated? X Yes No.		SWL		
Type of perforator used mills	MATERIAL			
Size of perforations 4 in. by 3 in.	Sand & Graver Drown	 -		
100 perforations from 20 ft. to 30 ft.	Sand & Graver			
perforations fromft. toft.	Sand	5		
perforations from ft. to ft.	Gravel & Sand 19 30			
(7) SCREENS: Well screen installed? Yes X No				
Manufacturer's Name		·		
Type Model No.				
Diam. Slot size Set from ft. to ft.				
Diam. Slot size Set from ft. to ft.				
Drawdown is amount water level is				
(8) WELL 12313. lowered below static level				
Was a pump test made? K Yes □ No If yes, by whom?				
Yield: 300 gal./min. with 13 ft. drawdown after 1 hrs.				
400 " 21 " 1 "				
" " "				
st drawdown after hrs.				
Danier test		<u></u>		
Artesian flow g.p.m.	Work started 5/26 1971 Completed 5/31/71	19		
perature of water Depth artesian flow encountered ft.	Work started $5/26$ 19/1 Completed $5/1/71$ 19 Date well drilling machine moved off of well $6/1/71$ 19			
(9) CONSTRUCTION:				
Don't and to	Drilling Machine Operator's Certification:	rwigion.		
Well Seal-Material about 18	This well was constructed under my direct supe Materials used and information reported above are tru	e to my		
Well sealed from land surface to				
Diameter of well bore to bottom of sealin. Diameter of well bore below sealin.	[Signed] Date 6/1/7/			
Number of sacks of cement used in well seal 110118 sacks Number of sacks of bentonite used in well seal 2 sacks	Drilling Machine Operator's License No.			
Number of sacks of pentonite used in weit sear	Water Well Contractor's Certification:			
Brand name of bentonite	This well was drilled under my jurisdiction and this	report is		
of water App. 50 lbs./100 gals	· I true to the best of my knowledge and benefit			
of water	Name DUFFIELD BROS. WATER WELLS INC.			
Did any strata contain unusable water? Yes X No	(Person, firm or corporation) (Type of print)			
	Address 1002 DIANNE DR. SE. SALEM, OF	و لندي		
Type of water.	-1/1 W/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/			
Method of sealing strata off	[Signed] Low and (Water Wyll Contractor)			
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	Contractor's License No. 15 Date 6/1/71	19		
Gravel placed from ft. to ft.		SP*45658-119		
	SHEETS IF NECESSARY)	~* ************************************		