NOTICE TO WATER WELL CONTRACTOR The original and first copy

RECEIVED

of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 973101 of well completion.

WATER WELL REPORT MAR 25 197 State Well No. 75 ZW-6

STATE OF OREGON
(Please type or print) ATER RESOURCES DEPT not write above this line) SALEM. CRECON

(1) OWNER:	(10) LOCATION OF WELL:	•
Name Mr. G.A. Sprong	County Marion Driller's well r	number 614 #2
Address 4275 Cloverdale Bd., Turner	SV 4 NE 4 Section 6 T.S	R. 2W W.1
(A) MUDE OF WORK (1 1)	Bearing and distance from section or subdivis	
(2) TYPE OF WORK (check):		
New Well Deepening Reconditioning Abandon □		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed v	vell
(3) TYPE OF WELL: (4) PROPOSED USE (check):		
Rotary Driven Domestic Industrial Municipal	•	135 1
Cable		surface. Date $3/15/'$
	Artesian pressure lbs. per squa	re inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well	below casing 6
6" Diam. from	Diameter of wen	
ft. to ft. Gage		
	Formation: Describe color, texture, grain size and show thickness and nature of each stratu	m and aquifer penetrated
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of forms	tion. Report each change is
	position of Static Water Level and indicate prin	icipal water-bearing strate
, pe of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	Ton soil	0' 4'
perforations from ft. to ft.	Clay (heavy tan)	4 7
perforations from	Clay (heavy orange)	7' 15'
perforations from	Clay (sticky blue)	15' 22'
(7) SCREENS: Well screen installed? ☐ Yes ■ No	Clay (sticky green)	22 35'
Manufacturer's Name	Clay (blue green)	35 60'
Type Model No.	Basalt (broken)	60' 65'
Diam. Slot size Set from ft. to ft.	Basalt (black)	65° 75°
Diam. Slot size Set from ft. to ft.	Basalt (black & brown)	
Set Holl It. w It.	broken in areas	75 150 1
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? Yes No If yes, by whom?		
Yield: gal./min. with ft. drawdown after hrs.		
" " "		
Air lift 20 gpm from 145° after 1 hr.		
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.	·	
reperature of water Depth artesian flow encountered ft.	Work started 3/10/76 19 Complete	ed 3/15/76 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	3/15/76 19 3/15/76 19
Well seal—Material usedCement	Drilling Machine Operator's Certification:	
Well sealed from land surface to	This well was constructed under my	direct supervision
Diameter of well bore to bottom of sealin.	Materials lised and information reported above are true to make	
Diameter of well bore below seal	best knowledge and belief.	- 1-
Number of codes of comment and to make 15	[Signet] Date 3/23, 19.76	
Number of sector of boots at	Drilling Machine Operator's License No320	
Brand name of bentonite sed in well seal sacks		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	· ·
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is	
Was a drive shoe used? ☐ Yes ② No Plugs Size: location ft.	true to the best of my knowledge and belief.	
Did any strata contain unusable water? Yes No	Name Pete Tolmasoff Well Drilling	
	(Person, firm or corporation)	(Type or print)
Type of water? depth of strata	Address	
Method of sealing strata off	[Signed] July o Stance	eso//
Was well gravel packed? Yes No Size of gravel:	(Water Well Contra	ctor)
Gravel placed from ft. to ft.	Contractor's License No. 410 Date 3	/23/76 19