

File Original and First Copy with the STATE ENGINEER, SALEM, OREGON

WATER WELL REPORT STATE OF OREGON

State Well No. 9/2W-12N State Permit No. G-1750

← Notice

M 1.21.....

14117 MARK

G-1771

(1) OWNER:

Name O.A. Cooms Address Rt. 1 Box 209 Jefferson, Ore.

(2) LOCATION OF WELL:

County Marion Owner's number, if any-- 1/4 1/4 Section T. R. W.M. Bearing and distance from section or subdivision corner

(3) TYPE OF WORK (check):

New Well [] Deepening [x] Reconditioning [] Abandon [] Abandonment, describe material and procedure in Item 11.

PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Irrigation [x] Test Well [] Other []

(5) TYPE OF WELL:

Rotary [] Cable [x] Dug [] Driven [] Jetted [] Bored []

(6) CASING INSTALLED:

8 5/8" Diam. from 80 ft. to 150 ft. Gage 250

(7) PERFORATIONS:

Perforated? [x] Yes [] No Type of perforator used Mills SIZE of perforations 5/16 in. by 2 in. 138 228 perforations from 83 ft. to 138 ft.

(8) SCREENS:

Well screen installed [] Yes [x] No Manufacturer's Name Model No. Slot size Set from ft. to ft.

(9) CONSTRUCTION:

Was well gravel packed? [] Yes [x] No Size of gravel: Gravel placed from ft. to ft. Was a surface seal provided? [] Yes [] No To what depth? ft. Material used in seal-- Did any strata contain unusable water? [] Yes [] No Type of water? Depth of strata Method of sealing strata off

(10) WATER LEVELS:

Static level 4 ft. below land surface Date 6/27/61 Artesian pressure lbs. per square inch Date

Log Accepted by: [Signature] [Signed] Date 7/31, 1961 (Owner)

(11) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [x] Yes [] No If yes, by whom? Stettler Yield: 310 gal./min. with 92 ft. drawdown after 1/2 hrs.

(12) WELL LOG:

Diameter of well 8x10 inches. Depth drilled 83 ft. Depth of completed well 166 ft. Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.

Table with columns MATERIAL, FROM, TO. Rows: Coarse gravel with clay pressed into it (83-153), Sandy clay (153-165), coarse gravel with clay (165-166)

It is my understanding this well was drilled and cased with 10" std pipe through coarse gravel from 0 83

The 10" casing was perforated from near the top to bottom.

RECEIVED JUL 31 1961 STATE ENGINEER SALEM, OREGON

Work started 6/12/61 19 Completed 6/27/61 19

(13) PUMP:

Manufacturer's Name Type: H.P.

Well Driller's Statement:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Harry A. Robinson (Person, firm, or corporation) (Type or print) Address 2214 N. Front St. Salem Driller's well number 9/2W-12N2 [Signed] Harry A. Robinson (Well Driller) License No. 22 Date 7/5, 1961