NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED OCT 22 1975 WATER RESOURCES DEPT. SALEM, OREGON

MARI 1425

MARI 1425

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

State Well No. 45/3w-1

State Permit No.

(1) OWNER:
Name Allen Jungwirth
Address Star Rt., Box 69
St. Paul, Ore. 97137

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED: Threaded ☐ Welded ☒
8" Diam. from +2 ft. to 121'1" ft. Gage .250
8 x 10" bell from 121'1" ft. to 121'4" ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used mills knife
Size of perforations 5/16 in. by 2 in.
120 perforations from 75 ft. to 80 ft.
240 perforations from 102 ft. to 112 ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
d: 115 gal./min. with 46 ft. drawdown after 4 hrs.
w/ air lift " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
esian flow g.p.m.
perature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION: Spudded in clay cuttings
Well seal—Material used
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 12 in.
Number of sacks of cement used in well seal - sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? - depth of strata -
Method of sealing strata off -
Was well gravel packed? ☒ Yes ~~☐ No~~ Size of gravel 3/4 - 3/8
Gravel placed from 20 - ft. to - 120 ft.

(10) LOCATION OF WELL:
County Marion Driller's well number 7506
¼ ¼ Section 1 T. 4S R. 3W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 15 ft.
Static level 28 ft. below land surface. Date 8-8-75
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing -
Depth drilled 120 ft. Depth of completed well 121'4" ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
top soil	0	3	
brown clay	3	15	
brown sandy clay	15	48	
blue green clay	48	77	
brown sandy clay	77	80	
brown clay	80	97	
brown sand some clay	97	103	
pea gravel	103	112	
blue clay	112	120	

Work started 7-30 19 75 Completed 9-25 19 75
Date well drilling machine moved off of well 9-25 19 75

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Edgar J. Mullen Date 10-20, 19 75
(Drilling Machine Operator)
Drilling Machine Operator's License No. 581

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Milo Schneider Equipment Co.
(Person, firm or corporation) (Type or print)
Address Star Rt., Box 97, St. Paul, Ore.
[Signed] Milo Schneider
(Water Well Contractor)
Contractor's License No. 387 Date 10-20-75, 19

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119