of this report are to be CEIVENTER WELL filed with the	L REPORT	95	/2w	-30
	M M (
	State Permit No	o		••••••
of well complet WATER RESOURCES DEPT	ove this line)			
SALEM OPECON	77)			
(1) OWNER:	(10) LOCATION OF WELL:		7/4	
Name Dina Madsen	County Marion Driller's well nu			1075K
Address Rt. 1, Box 378P	NE 34 SW 34 Section 30 T. 9S	R. 2V	ł	W.M.
Jefferson, Or. 97352	Bearing and distance from section or subdivision	n corne		
(2) TYPE OF WORK (check):	Dealing and distance from Section of Sabaty Br	Jan Corne	· .	
· · · · · · · · · · · · · · · · · · ·		•		
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐ If abandonment, describe material and procedure in Item 12.				
	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 77 ft.			
Rotary Driven Domestic N Industrial Municipal	Static level 30 ft. below land s	urface.	Date 10	-8-75
Cable				
Dug Dored D Mildaron D Less were D Cares	Artesian pressure lbs. per squar	e men.	Date	
CASING INSTALLED: Threaded Welded 1	(12) WELL LOG: Diameter of well by	_	8	11
Diam. fromft. toft. Gage	Carry Transcript Summerer of West N		mg	
" Diam. from ft. to ft. Gage	Depth drilled 100 ft. Depth of comple	eted well	100	ft.
" Diam, from ft. to ft. Gage	Formation: Describe color, texture, grain size s			
Diam. from	and show thickness and nature of each stratur with at least one entry for each change of format			
PERFORATIONS: Perforated? • Yes • No.	position of Static Water Level and indicate prin			
A continued and	MATERIAL	From	То	SWL
1/1, 000000				
Size of perforations in. by in.	light brown clay	0	15	
perforations fromft. toft.	grey clay stone	15	24	
perforations from ft. to ft.	grey sandstone	24;	32	
perforations from ft. to ft.	grey clay stone	32	100	30
(a) CODEENC				
(7) SCREENS: Well screen installed? ☐ Yes 🛱 No				
Manufacturer's Name				
Type Model No				
Diam Slot size Set from ft. to ft.				
Diam. Slot size Set from ft. to ft.				
(2) WITH TESTS. Drawdown is amount water level is				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? ☐ Yes ☒ No If yes, by whom?				
Yield: gal./min. with ft. drawdown after hrs.				
" " "				
ATR " "				
28 test 75 gal./min. with 55 ft. drawdown after 2 hrs.				
Artesian flow g.p.m.				
	Work started 10-7 19 75 Complete		10-8	19 75
erature of water 53 Depth artesian flow encountered ft.		eu		
(9) CONSTRUCTION:	Date well drilling machine moved off of well		10_	8 ¹⁹ 75
•	Drilling Machine Operator's Certification:			
Well seal—Material used 65	This well was constructed under my	direct	super	vision.
Well sealed from land surface to ft.	Materials used and information reported			
Diameter of well bore to bottom of seal	best knowledge and belief.	A	9/2	
Diameter of well bore below seal in. 19	[Signed] (Drilling Macrille progrator)	Date !!	2 fZ	., 19:32.
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.		951	
Number of sacks of bentonite used in well seal sacks	Dilling Muchinic Operator & Internse 140.			
Brand name of bentonite	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons	1	iotion s	nd thin -	enort is
of water	This well was drilled under my jurisd true to the best of my knowledge and bel	ief.	ra uns I	CPOL 18
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.	Schoen Electric & Pump			
Did any strata contain unusable water? Yes No	Name (Person, firm or corporation)	(T	ype or pri	nt)
Type of water? depth of strata	Address 626 W Queen Avenue - A	lbany	, Or.	97321
	La & Nolan	lan.		
Method of sealing strata off	[Signed]			
Was well gravel packed? ★ Yes No Size of gravel: 1/2-gravel	(Water Well Conti	In /	4	70
Gravel placed from65 ft. to100 ft.	Contractor's License No	10/	7	, 19.//