NOTICE TO WATER WELL CONTRACTOR

The original and first copy!

MAY 17 19 WATER WELL REPORT

STATE ENGINEER, SALEM, OREDON AND STATE OF OREGON within 30 days from the date of well completion.

State Permit No.

Cobbles-clay (firm)	after ? Ye	hrs " hrs " hrs 8 15
Was a pump test made: \$\frac{\text{T}}{2} \text{ Per} \backsty \text{ Norm} \frac{\text{S}}{2} \text{ Norm} \frac{\text{T}}{2} \text{ Norm} \frac{\text{S}}{2}	after ? Ye struct naterial e of fo	hrs " hrs as a No ses a No ses a No ture, and ture, and tin each ormation TO 2' 8' 15' 21' 22'
Tarracy of	after ? Ye 2: I struct naterial e of fo	hrs S ft ture, and l in each rmation TO 2' 8' 15' d 21' 22'
County Marion Driller's well number 170 SE SE W.M.	? Ye	hrs S ft ture, and l in each rmation TO 2' 8' 15' d 21' 22'
County Maxion Driller's well number 170 Maxion Depth drilled Driller's well number 170 Driven D	? Ye	3 ft ture, and l in each romation TO 2' 8' 15' 21' 22'
County Marion Driller's well number 170 MR 14 M 14 Section 33 T. 18 R. 28 W.M. Bearing and distance from section or subdivision corner County Maring and distance from section or subdivision corner	? Ye	3 ft ture, and l in each romation TO 2' 8' 15' 21' 22'
Rearing and distance from section or subdivision corner Comparison	structuraterials of form	3 ft ture, and l in each remation TO 2' 8' 15' d 21' 22'
Bearing and distance from section or subdivision corner Compared to the perforations from the fit to the perforations from the tother perforations from the perforations from the tother perforations from the perforations from t	structuraterials of form	3 ft ture, and l in each remation TO 2' 8' 15' d 21' 22'
Call	l struct naterial e of fo OM 2' 2' 8'	ture, and line each romation TO 2' 8' 15' 21' 22'
Abandonnent, describe material and procedure in item 12.	struction attention at the struction attention at the structure at the str	TO S' 15' d 21' 22'
MATERIAL FROM STATE Separation Abandon Abandon Abandon Abandonment, describe material and procedure in item 12.	ом 2' 8' 2по	то 2' 8' 15' d 21' 22'
MATERIAL FROM STATE Separation Abandon Abandon Abandon Abandonment, describe material and procedure in item 12.	ом 2' 8' 2по	то 2' 8' 15' d 21' 22'
(3) TYPE OF WORK (check): Weil B Deepening Reconditioning Abandon A	2' 8' and 5'	2' 8' 15' d 21' 22'
(3) TYPE OF WORK (check): Weil B Deepening Reconditioning Abandon A	2' 8' and 5'	2' 8' 15' d 21' 22'
Abandonment, describe material and procedure in Item 12.	and 5	8' 15' d 21' 22'
Cobbles-clay (firm)	and 5	15' d 21' 22'
Note	5' 1'	d 21' 22'
Domestic Industrial Municipal Rotary Driven Cable E Jetted Dug Bored General Stand (packed - medium) 2 General Stand (packed -	1.	22'
Sand (packed - medium) 2 3 3 3 3 3 3 3 3 3		22'
CASING INSTALLED: Threaded Welded		
(6) CASING INSTALLED: Threaded		
## Diam from ## Office of the control of the cont		
"Diam from		
"Diam from ft. to ft. Gage (7) PERFORATIONS: Perforated? X Yes \(\) No Type of perforator used Act Torch Size of perforations from ft. to ft. perforations from ft. perforations from ft. to ft. perforations from ft.		
(7) PERFORATIONS: Perforated? Yes No Type of perforator used		
Type of perforator used Act Torch Size of perforations in. by 12 in. 60 perforations from 23 ft. to 18 ft. perforations from 5t. to 5t. Work started 4/25/6619 Completed 4/26/60 Date well drilling machine moved off of well 4/26/60 (13) PUMP: Manufacturer's Name 5t. Type: 5t. 5t. Ty		
Size of perforations in. by 12 in. 50 perforations from 23 ft. to 18 ft. perforations from ft. to ft. Work started 4/25/6619 Completed 4/26/619 patential ft. Was a packer used? Manufacturer's Name ft. Topic ft. Topic ft. Topic ft. ft. Manufacturer's Name ft. ft. Topic ft. ft. ft. perforations from ft. to ft. More started ft. ft		
Solution		
perforations from ft. to ft. [8] SCREENS: Well screen installed? Yes No Manufacturer's Name Model No. Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft. [9] CONSTRUCTION: Work started 4/25/6619 Completed 4/26/619 Date well drilling machine moved off of well 4/26/619 [13] PUMP: Manufacturer's Name Type: Manufacturer's Name Type: H.P.		
perforations from ft. to ft.	1	
perforations fromft. toft. to	1	
SCREENS: Well screen installed? Yes		
(8) SCREENS: Well screen installed?		
Model No. Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft. O) CONSTRUCTION: Well seal—Material used in seal bentonite Depth of seal 18 ft. Was a packer used? Diameter of well bore to bottom of seal 10 in.		
Model No. Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft. O(9) CONSTRUCTION: Well seal—Material used in seal ft. Was a packer used? Diameter of well bore to bottom of seal 10 in.		
Model No. Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft. O(9) CONSTRUCTION: Well seal—Material used in seal bentonite Depth of seal 18 ft. Was a packer used? 19 Diameter of well bore to bottom of seal 10 in.	\bot	
Diam. Slot size Set from ft. to ft. Date well drilling machine moved off of well 4/26/66 (13) PUMP: Well seal—Material used in seal ft. Was a packer used? Name Diameter of well bore to bottom of seal 10 in.		
Diam. Slot size Set from ft. to street 1/20/669 Completed 1/26/69 CONSTRUCTION: Well seal—Material used in seal Bentonite Depth of seal 18 ft. Was a packer used? 19 Manufacturer's Name Type: H.P.	100	
(9) CONSTRUCTION: Well seal—Material used in seal Bentonite Depth of seal 18 ft. Was a packer used? Diameter of well bore to bottom of seal 10 in.		19
Well seal—Material used in seal Bentonite Depth of seal 18 ft. Was a packer used? 10 in. Manufacturer's Name Type: H.P.	<u>6</u>	19
Depth of seal		
Depth of seal		
Diameter of well bore to bottom of seal 10 in.		
Were any loose strata cemented off? Yes No Depth		
Was a drive shoe used? Yes □ No This well was drilled under my jurisdiction and t	his re	eport is
Was well gravel packed? Yes No Size of gravel: true to the best of my knowledge and belief.		
Gravel placed from ft. to ft. NAME Pete Tolmasoff Well Brilli	ne	
Did any strata contain unusable water? Tyes To No (Person, firm or corporation) (Type or particular type or	print)	••••••
Type of water? depth of strata Address Turner, Ore.	••••••	*************
Mathod of sealing strata off		
(10) WATER LEVELS: Drilling Machine Operator's License No. 320		
[Signed] Later a later	· ···	
Static level 9 ft. below land surface Date 4/28/56 (Water Well Contractor)	<u></u>	 2
Artesian pressure lbs. per square inch Date Contractor's License No. 410 Date 4/28/66	H	2