NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

/ (Please type or print)

(Do not write above this line)

RECEIVED ... 95/3W-1ca

WATER RESOURCES DEPT.
SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name Brief Rosback	County Marion. Driller's well number 6-49-77.
Address 2031 Rames S.E.	N.E 4 S.W4 Section 1 T. 95 R. 310. W.M.
(9) TWDE OF WORK (short)	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well 🖳 Deepening 🗌 Reconditioning 🗍 Abandon 🗌 If abandonment, describe material and procedure in Item 12.	
	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 330 ft.
Cable	Static level 302 ft. below land surface. Date 23.7
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing
	Depth drilled 425 ft. Depth of completed well 425. ft.
	Formation: Describe color, texture, grain size and structure of materials:
" Diam, from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes PANo.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Red Clay 0 10
perforations from ft. to ft.	Belders' Clay 10 15
perforations fromft. toft.	Red Clay 15 30
perforations from ft. to ft.	Tan Clay 30 42
(7) SCREENS: Well screen installed? Yes No	Ked Clay 92 65
Manufacturer's Name	Peremposed Rocks 65 84 Rasalt Korbs. 84 90
Type Model No	Rosalt Role Some Bolion 90 200
Diam Slot size Set from ft. to ft.	-Busult Rode. 200 280
Diam Slot size Set from ft. to ft.	Basalt Broken 230 265
(8) WELL TESTS: Drawdown is amount water level is	Basult Korle 765 320
lowered below static level	Bosalt Kode Hongeonb. 320 420 302
Was a pump test made? Yes No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	4" PUC liner installed 50 -420'
" -1 8410' "	Per 4x6-80 Per 340-420:
Air. Stemar.	
A	
Artesian flow g.p.m. perature of water Depth artesian flow encounteredft.	Work started Dec: 12 1922. Completed Dec. 2.3 1977
	Work started 1/2 1999. Completed 1/20. 23 1999 Date well drilling machine moved off of well 1999
(9) CONSTRUCTION:	
Well seal-Material used Connend	Drilling Machine Operator's Certification: This well was constructed under my direct supervision.
Well sealed from land surface to ft. Diameter of well bore to bottom of seal in.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	Industrial additional of 27 77
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)
How was cement grout placed?	Drilling Machine Operator's License No
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? ☐ Yes X No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water? Yes Yes You	Name Gerson, firm or corporation (Type or print)
Type of water? depth of strata	Address 11401 Ston tramp Rd S.E. Amsy, 11t, O
Method of sealing strata off	7 DE TE
Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well Contraditor)
Gravel placed fromft. toft.	Contractor's License No. 75 Date 27 , 1927
	, and the state of