NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

MARI 15026 E G E I V E

10	s/3W	-12
<u>9's</u>		-11

STATE ENGINEER, SALEM, OREGON 17310 within 30 days from the date of well completion.

TER WELL REPORTOCT 3 1 1972	95/311-11
STATE OF OREGONATE ENGINEER (Please type or print) SALEM. OREGISTATE	Well No.
SALEM. OREGISTATE	Permit No.
o not write above this line)	

	 	
(1) OWNER:	(10) LOCATION OF WELL:	•
Name Jefferson City Water Dist.	County Marion Driller's well no	umber
Address Jefferson, Ore.	% % Section 11 T. 9S	R. 3W W.M.
	Bearing and distance from section or subdivisi	
(2) TYPE OF WORK (check):		
New Well Deepening □ Reconditioning □ Abandon □		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	vell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 2	
Rotary Driven Domestic Industrial Municipal		surface. Date 10-9-72
Cable K Jetted Domestic Industrial Mulnicipal K Dug Bored Irrigation Test Well Other	Artesian pressure Ibs. per square	
CASING INSTALLED: 12 "Diam from +1' ft to 41'08" ft Gage 250Wall "Diam from ft to ft Gage	Depth drilled 43 ft. Depth of compl	
PERFORATIONS: Perforated? ₩ Yes □ No.	Formation: Describe color, texture, grain size and show thickness and nature of each stratum with at least one entry for each change of formation of Static Water Level and indicate prince	m and aquifer penetrated, tion. Report each change in
Type of perforator used Acetylene Torch	MATERIAL	From To SWL
Size of perforations ½ in. by 12 in.		0 2
110 perforations from 29'08" ft. to 41'08" ft.	Top Soil Sandy Loam	2 10
perforations fromft. toft.	Dirty Large Gravel	10 26
perforations from	Brown Sand & Large Gravel	26 33
	Brown Sandy Clay & Gravel	33 341/2
(7) SCREENS: Well screen installed? Yes No	Brown Sand & Large Gravel	341/2 38
Manufacturer's Name	Brown Sandy Clay & Gravel	38 43
Type Model No.		
Diam. Slot size		
Diam. Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		 - -
Was a pump test made? Yes □ No If yes, by whom? Self		
Yield: 300 gal./min. with 131/2 ft. drawdown after 48 hrs.		
" " "		
<i>" " "</i>		
Bailer test gal./min. with his.		
Artesian flow g.p.m.		
perature of water Depth artesian flow encountered ft.	Work started 10-3 1972 Complete	ed 10-9 1972
(9) CONSTRUCTION:	Date well drilling machine moved off of well	10-9 1972
Well seal-Material used Cement	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported	
Diameter of well bore to bottom of seal in.	best knowledge and belief.	
Diameter of well bore below seal12 in.	[Signed] (Drilling Machine Operator)	Date / 0 / 20 , 19 / 2
Number of sacks of cement used in well seal Sacks	Drilling Machine Operator's License No.	436
Number of sacks of bentonite used in well seal sacks		
Brand name of bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisd	
of waterlbs./100 gals. Was a drive shoe used? XYes \(\sigma\) No Plugs Size: location ft.	true to the best of my knowledge and bel	
Did any strata contain unusable water? Yes No	Name Merle Warren Well Dril	ling
Type of water? depth of strata	Address Rt.), Box 84, Tangen	
Method of sealing strata off	March 111-11	
***	[Signed] (Water Well Control	ractor)
	Contractor's License No. 182 Date	/
Gravel placed from ft. to ft.	Contractor a Diceipe No Date	