NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

MARION 15116

State Well No. 9S/3W-22
State Permit No.

(1) OWNER:
Name DENNIS STORTZ
Address 2376 FAIRGROUNDS RD NE
SALEM, OR 97300

(2) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☑ Driven ☐
[illegible] ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☑ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☑
6" Diam. from +1 ft. to 19 ft. Gage .250
[illegible]" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☐ Yes ☑ No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☑ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
[illegible] a pump test made? ☐ Yes ☑ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
W/AIR 10 gpm " "
[illegible]er test gal./min. with 200 ft. drawdown after 1 hrs.
Artesian flow X g.p.m.
Temperature of water 51° Depth artesian flow encountered — ft.

(9) CONSTRUCTION:
Well seal—Material used CEMENT
Well sealed from land surface to 19 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 6 sacks
How was cement grout placed? PRESSURE GROUT

Was a drive shoe used? ☐ Yes ☑ No Plugs NO Size: location ft.
Did any strata contain unusable water? ☐ Yes ☑ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☑ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County MARION Driller's well number 1381
¼ ¼ Section 22 T. 9S R. 3W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 430 ft.
Static level 330 ft. below land surface. Date 9-18-79
Artesian pressure X lbs. per square inch. Date —

(12) WELL LOG: Diameter of well below casing 6"
Depth drilled 530 ft. Depth of completed well 530 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
TOPSOIL	0	1	
BROWN CLAY	1	3	
BROWN SANDSTONE	3	45	
BLUE SANDSTONE	45	530	

RECEIVED
OCT 11 1979
WATER RESOURCES DEPT
SALEM, OREGON

Work started 9-18 19 79 Completed 9-19 19 79
Date well drilling machine moved off of well 9-19 19 79

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Claude Irby (Drilling Machine Operator) Date 9-24, 19 79
Drilling Machine Operator's License No. 1133

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name BERT JONES (Person, firm or corporation) (Type or print)
Address 29400 SANTIAM HWY, LEBANON, OR 97355
[Signed] Bert Jones (Water Well Contractor)
Contractor's License No. 514 Date 9-24, 19 79

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119