NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

MART..... 15146

State Well No. 9s/3w-23
State Permit No.

(1) OWNER:
Name Adam Mercado
Address Rt 1 Box 49 C
Jefferson, Oregon 97352

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED: Threaded ☐ Welded ☒
6" Diam. from +1 ft. to 21 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS: Perforated? ☐ Yes ☒ No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " "
"Tested W/Air" 7 gpm " "
Bailer test gal./min. with 85 ft. drawdown after 1 hrs.
Artesian flow — g.p.m.
Temperature of water 51° Depth artesian flow encountered — ft.

(9) CONSTRUCTION:
Well seal—Material used Cement
Well sealed from land surface to 21 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 6 sacks
How was cement grout placed? pumped pressure grout
Was a drive shoe used? ☒ Yes ☐ No Plugs No Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County MARION Driller's well number 1305
¼ ¼ Section 23 T. 9S R. 3W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 190 ft.
Static level 160 ft. below land surface. Date 7-5-79
Artesian pressure — lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6"
Depth drilled 245 ft. Depth of completed well 245 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Brown Clay	0	1	
Brown Sandstone	1	42	
Blue Sandstone	42	43	
Brown Sandstone	43	47	
Blue Sandstone	47	51	
Brown Sandstone	51	56	
Blue Sandstone	56	245	

RECEIVED
JUL 20 1979
WATER RESOURCES DEPT
SALEM, OREGON

Work started 7-5 1979 Completed 7-6 1979
Date well drilling machine moved off of well 7-6 1979

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Claude Doty (Drilling Machine Operator) Date 7-10, 1979
Drilling Machine Operator's License No. 1133

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Bert Jones (Person, firm or corporation) (Type or print)
Address 29400 Santiam Hwy Lebanon, Oregon
[Signed] Bert Jones (Water Well Contractor)
Contractor's License No. 514 Date 7-10, 1979

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119