NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER OF CONTRACTOR

Sta

5/1W-X

STATE ENGINEER, SALEM, OREGOTION ENGINEER OF OREGON within 30 days from the date of well completion.

SALEM OREGONESSE type or print)

of well completion. SALEM OREGONease ty	pe or print) State Permit No	**************
(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level	
Name Bronic Bros.	Was a pump test made? Yes No If yes, by whom? dri	ller
Address Hubbard, Oregon	Yield: 500 gal./min. with 72 ft, drawdown after	8 hrs.
	<u>" 600 " 85 "</u>	8 "
(2) LOCATION OF WELL:		. 4 "
County Marian Driller's well number	Bailer test gal./min, with ft. drawdown afte	r hrs.
F FG 3.11	Artesian flow g.p.m. Date	
34 % Section 5 T. 5S R. 1W W.M.	Temperature of water Was a chemical analysis made?	Yes 😡 No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below casing	
	Diameter of well below casing	**************************
grand was a second of the seco		L31 ft.
	Formation: Describe by color, character, size of material and st show thickness of aquifiers and the kind and nature of the mate stratum penetrated, with at least one entry for each change of	ructure, and
	stratum penetrated, with at least one entry for each change o	f formation.
	MATERIAL FROM	
(3) TYPE OF WORK (check):		I TO
New Well Deepening □ Reconditioning □ Abandon □	_Surface 0	
ndonment, describe material and procedure in Item 12.	Brown sandy clay 3	37
	Blue sandy clay 37	68
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Small gravel 68	70
Domestic Industrial Municipal Rotary Driven	Blue sandy clay 70	99
Cable 🖸 Jetted 🗍	Black sand 99	107
rrigation 🖸 Test Well 🗌 Other 🔲 Dug 🗍 Bored 🗍	Broken gravel 10%	124
(6) CASING INSTALLED: Threaded □ Welded ☑	Blue clay 124	131
16 " Diam, from 0 ft. to 131 ft. Gage 14"	1	- 12)1
" Diam. fromft. toft. Gage		
(7) PERFORATIONS: Perforated? Yes No		
Type of perforator used Millknife		
Size of perforations 3/8 in. by 2 in.		
358 perforations from 108 ft. to 124 ft.		
perforations from ft. to ft.		
perforations fromft. toft.	The state of the s	1
perforations fromft. toft.		
perforations fromft. toft.		
(A) CONTINUE		 -
(8) SCREENS: Well screen installed? ☐ Yes 🗓 No		
Wanufacturer's Name		-
Model No.		-
h. Slot size Set from ft. to ft.	Work started Nov 16 1964, Completed Jan 15	1965
Diam Slot size Set from ft. to ft.	Date well drilling machine moved off of well	
(9) CONSTRUCTION:		19
	(13) PUMP:	
Well seal—Material used in seal Pudn 16 Mud	Manufacturer's Name	
Depth of seal 20 ft. Was a packer used? NO	Туре: Н.Р	***************************************
Diameter of well bore to bottom of seal20 in.		
Were any loose strata cemented off? Tyes No Depth	Water Well Contractor's Certification:	-
Was a drive shoe used? ☐ Yes ☒ No 🚊	This well was drilled under my jurisdiction and this	roport in
Was well gravel packed? ☐ Yes 🏋 No Size of gravel:	true to the best of my knowledge and belief.	
Gravel placed fromft. 6ft.	7 1 77	
Did any strata contain unusuable water 🔲 Yes 🙇 No	NAME John Truman Miller (Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address P O Box 42 Hubbard, Oregon	
Method of sealing strata off	The state of the s	
	Drilling Machine Operator's License No. 277 16	**************
(10) WATER DEVELS.		
Static level 16 ft. below land surface Date 1/15/65	[Signed] (Water Well Contractor)	******
Artesian pressure Ibs. per square inch Date		
(USE ADDITIONAL STI	Contractor's License No. 26 Date Feb 6	, 19.65.