NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the
WATER RESOURCES DEPARTMENT.
WATER RESOURCES DEPARTMENT.
STATE OF OREGON

SALEM, OREGON 97310

within 30 days from the date

Gravel placed from ...... ft. to ..... ft.

**MARI 15504** 

WATER WELL REPORT

JUN 25 1980 (Please type or print)

of well completion. WATER RESOURCES DEPT SALEM, OREGON (10) LOCATION OF WELL: (1) OWNER: Marion Paul Vettrus Driller's well number Name County 8372 Enchanted Way S.E. 36 <sub>T.</sub> 98 14 Section Turner, Oregon Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): New Well X Deepening [ Reconditioning | Abandon | If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found Petary Driven 🛘 Domestic Maintain Municipal Static level ft, below land surface. Date Jetted 🔲 le Bored 🔲 Irrigation □ Test Well □ Other Artesian pressure lbs. per square inch. Date 75) CASING INSTALLED: CASING INSTALLED: Threaded Welded 4 250 **+**⊕ 6 (12) WELL LOG: Diameter of well below casing .. 188 Depth drilled ft. Depth of completed well Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in PERFORATIONS: position of Static Water Level and indicate principal water-bearing strata. Perforated? Yes No. .ype of perforator used MATERIAL Top. Soil Size of perforations in. by 1 8 Red Caly ...... perforations from ....... ft. to ..... ft. Tan Clay 8 26 \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Gray Clayy 26 perforations from \_\_\_\_\_ ft. to \_\_\_\_\_ 32 Decomposed Rock (7) SCREENS: Well screen installed? ☐ Yes ☐ No Pumice Manufacturer's Name 64 80 Gray Basalt Blue Basalt 80 86 Diam. Slot size Set from ft. to ft. Black Basalt 86 150 Diam. Slot size Set from ft. to ft. 150 Lightt Gray Basalt 160 160 188 Dark Gray Basalt (8) WELL TESTS: Drawdown is amount water level is lowered below static level a pump test made? 

Yes X No If yes, by whom? 82 ft. 2 G.P.M. Water Bearing <u> 132 - 136</u> 15 G.P.M. Yield: gal./min. with ft. drawdown after hrs. 168 - 173 Water Bearing <u> 25 GlP.M.</u> "Air test - may "fluctuate 42 gal./min. with 165 ft. drawdown after Artesian flow g.p.m. perature of water Depth artesian flow encountered ...... 4/2 19 80 Completed Work started Date well drilling machine moved off of well (9) CONSTRUCTION: Well seal-Material used Portland Cement Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Diameter of well bore below seal 6 10 in Motoate 4/4, 19 80 [Signed] ........ (Drilling Machine Operator) Number of sacks of cement used in well seal ..... Drilling Machine Operator's License No. 1103 How was cement grout placed? Air Grout Pump Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name Miller & West Well Drilling
(Type or print) Was a drive shoe used? Yes I No Plugs ...... Size: location ......... Did any strata contain unusable water? 🗌 Yes 💆 No (Person, firm or corporation) 5875 Gaffin Rd. S.E. Salem Type of water? depth of strata Method of sealing strata off (Water Well Contractor) Was well gravel packed? ☐ Yes 🖔 No Size of gravel: .......... Contractor's License No. 746 Date

(USE ADDITIONAL, SHEETS IF NECESSARY)