The original and first copy of this report are to be filed with the	L REPORTARIO. State Well No. 9	1-3chde
STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion. (Please type (Do not write about the completion)	or print)	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
(1) OWNED.	(10) LOCATION OF WELL:	
(1) OWNER:	County MAr/On Driller's well number	
Name FTZel Bros.		
Address RT/ BOX 300 STRYTON CONSERVE 92383	14 14 Section 3 T. 95 R.	<u>k</u> w.m.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corne	<u>r</u> : -
4	to at the	
New Well Deepening Reconditioning Abandon Abandon		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 38	ft.
Rotary 🚺 Driven 🗌 Domestic 📙 Industrial 🗎 Municipal 🗎	Static level 2/ ft. below land surface.	Date 5-15-20
Cable	Artesian pressure lbs. per square inch.	Date
		m 61
CASING INSTALLED: Threaded To Welded To	(12) WELL LOG: Diameter of well below case	. رست
10 " Diam from 0 1 ft. to 109 ft. Gage 250	Depth drilled 300 ft. Depth of completed wel	1 306 ft.
5 " Diam. from 92 ft. to 206 ft. Gage 250	Formation: Describe color, texture, grain size and struc	
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and a with at least one entry for each change of formation. Rep	
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal wa	
Type of perforator used Mills Knife 742 to 95, 3 X22	MATERIAL From	To SWL
Size of perforations 34 in. by 6" in.	Co.'/	/
29/ 7/1/4 93	Clay (Brown) 1	8
211 98	Wearthand out Rock 8	18
perforations from 2 ft. to 15 ft. 4 P perforations from 123 ft. to 164 ft.	CLAN (Blue) 18	24
80 164 204	CLAY (GrAV) 24	26
(7) SCREENS: Well screen installed? Yes M No	tuffstone & Bouldere 26	38
Manufacturer's Name	Gravel 38	100
Type Model No.	Broken + WeArtherd out RoeNoo	108
Diam. Slot size Set from ft. to ft.	BASAIT Broken 108	132
Diam. Slot size Set from ft. to ft.	BASA1+ 132	165
(8) WELL TESTS: Drawdown is amount water level is	Claystone Blue green) 165	12%
lowered below state level	Clay Stone (Brown Broken) 7%	205
Was a pump test made? Yes \(\subseteq \) No If yes, by whom? Sniete	BASAIX 208	223
Vield: 275 gal./min. with 200 ft. drawdown after 7 hrs.	CAY (bavender) 23 Clay (bight Brown) 226	252
" " "	Tuffaceous 252	300
и и и	-Tarrage	
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
Depth artesian flow encountered ft.	Work started 4-7 19 72 Completed 5-	-15 1972
	Date well drilling machine moved off of well	15 19 22
(9) CONSTRUCTION:		
Well seal-Material used Cement Gracet	Drilling Machine Operator's Certification: This well was constructed under my direc	t sunervision.
Well sealed from land surface toft.	Materials used and information reported above	are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.	
Diameter of well bore below seal	[Signed] Aut the Bernell Date 5-25, 19.72	
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No. 28 9	
Number of sacks of bentonite used in well seal sacks		
Brand name of bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is	
was a drive shoe used? ✓ Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief.	
Did any strata contain unusable water? Yes No	Name XObinson Fold Well (Person, firm or corporation)	ype or print)
Type of water? depth of strata	Address 4510 DAILAS HWY	Alem over
	9 , 7/ 000	, , , , , ,
Method of sealing strata off Was well gravel packed? Yes □ No Size of gravel: Yes □ No Size of gravel:	[Signed] (Water Well Contractor)	
Gravel placed from 4.7 ft. to 20 ft.	Contractor's License No Date	5 1972
CARTOL PROOF LIVER INFORMATION LIVE W INSTERNATION LIVE	1	