M 1 3 ... (559) NOTICE TO WATER WELL CONTRACTOR The original and first corporation of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97316 6 1965 STATE OF OREGON (Please type or print) of well completion.

9/1-5N(1)

of well completion. A LE ENGINE	rpe or print) 3454 State Permit No		
(1) OWNER: SALEM OREGON	(11) WELL TESTS: Drawdown is amount water level is lowered below static level		
Name Della C. Boedigheimer	Was a pump test made? Yes \(\bar{\sqrt{1}}\) No If yes, by whom		
Address Rt.1 Box 328	Yield: 325 gal./min. with 15 ft. drawdov		hrs.
Stayton, Ore.	H " "		"
(2) LOCATION OF WELL:	" "		"
	Bailer test gal./min. with ft. drawdo	wn after	hrs.
County Marion Driller's well number 9/1-5N	Artesian flow g.p.m. Date		
1/4 1/4 Section T. R. W.M.	Temperature of water Was a chemical analysis made? Yes No		
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below ca	sing 1)
	Depth drilled 352 ft. Depth of completed we	<u> 11 352</u>) <u>ft.</u>
	Formation: Describe by color, character, size of materia show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each c	l and stru the mater hange of	cture, and al in each formation.
	MATERIAL	FROM	то
(3) TYPE OF WORK (check):	Top soil & clay	0	21
Well 🖪 Deepening 🗌 Reconditioning 🗍 Abandon 🖂	Basalt (fresh)	2븀	145_
indonment, describe material and procedure in Item 12.	Old land surface	115	165
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Decomposed vegetation	165	170_
Potomy G Driven G	Buckshot gravel & clay	170	195
Domestic industrial Municipal Cable 19 Jetted	Brwn sandstone	195	230
irrigation N Test Well Other Dug Bored	Blk	230	2/13
(6) CASING INSTALLED: Threaded Welded W	Andesite or basalt(very		45
(6) CASING INSTALLED: Threaded Welded X 103/4." Diam. from 150 ft. to 19 ft. Gage 250	hard)	2/13	352
•	/		
"Diam. from ft. to ft. Gage			
ft. to			
(7) PERFORATIONS: Perforated? ☐ Yes ☐ No	Hole leading off below		
Type of perforator used	284 ft.		
Size of perforations in. by in.	Reduced from 10" to 8"		
perforations from ft. to ft.	hole at 336 ft.		
ft. to ft.			
ft. to ft.	Do not use over 8" bowl		
perforations from ft. to ft.	assembly on pump.		
perforations from ft. to ft.			
(8) SCREENS: Well screen installed? ☐ Yes ➡ No			
To Manage			
Manufacturer's Name			
Model No.			
Slot size St. ft. to ft.	Work started \$\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	12/2/	<u>65 19</u>
Diam. Slot size Set from ft. to ft.	Date well drilling machine moved off of well 12	2/65	19
(9) CONSTRUCTION:	(13) PUMP:		
Well seal—Material used in seal Coment & drill cutting	S Manufacturer's Name		***************************************
Depth of seal	Type: H.P.		
Diameter of well bore to bottom of seal in.	Window Will Control don't Contification		
Were any loose strata cemented off? 🗌 Yes 🗶 No Depth	Water Well Contractor's Certification:		
Was a drive shoe used? 🗌 Yes 🎇 No	This well was drilled under my jurisdiction	and this	report is
Was well gravel packed? ☐ Yes K No Size of gravel:	true to the best of my knowledge and belief.		
Gravel placed from ft. to ft.	NAME Harry A. Robinson		
Did any strata contain unusable water? 🏻 Yes 🗘 No	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address 2214 Front NE Salem, Ore.		
Method of sealing strata off			
(10) WATER LEVELS:	Drilling Machine Operator's License No3		
(/	[Signed] Starry a Robin	ŝon	
Static level 193 ft. below land surface Date 12/2/6	(Water Well Contractor)		
Artesian pressure lbs. per square inch Date	Contractor's License No. 22 Date 7	0/0/6	٠ 10