NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

WATER WELL REPORT DE CENTRAL Well Do.

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF OREGON (Please type or print)

STATE OF OREGON		***************************************
(Please type or print)	JUL 2 G 1976 Fermit No	95/15-8
(Do not write above this line) [V.TER RESOURCES DED	

	E A F Ima			
(1) OWNER:	(10) LOCATION OF WELLSON			1 =
Name Leonard Ackler-	County Marion - Driller's well nu	mber 5	84-2	V .
Address 13	34 34 Section 8 T. 25	R. 1 E		W.M.
Humsylla De	Bearing and distance from section or subdivision	on corner		u
(2) TYPE OF WORK (check):	Bearing and distance from section of subdivision	/II COLLICE		······ 27-
New Well				
If abandonment, describe material and procedure in Item 12.		11		
	(11) WATER LEVEL: Completed w	eII.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	<u> </u>		ft.
Rotary M Driven Domestic M Industrial Municipal Cable Detect Industrial Municipal	Static level ft. below land s	urface.	Date M	rel 25,19
Dug Bored I Irrigation Test Well Other	Artesian pressure lbs. per squar	e inch.	Date	
CASING INSTALLED: Threaded Welded Welded Gage 250 Th. to Th. Gage 250 Th. to Th. Gage 250 Th. to Th. Gage Th. Ga	(12) WELL LOG: Diameter of well below casing Depth drilled 225 ft. Depth of completed well 225 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.			
Type of perforator used	MATERIAL	From	То	SWL
	Soil	0	3/5	
	Boken Rock	31/2	15	
perforations fromft. toft.	Class	15	25	
perforations fromft. toft.	Roldres a	2.5	35	
perforations from ft. to ft.	Solders.	772	40	
(7) SCREENS: Well screen installed? ☐ Yes ☑ No	Small Gravel	40	55	
Manufacturer's Name	A grave	55	90	
Type Model No	Party Mary	90	11.5	
Diam. Slot size Set from ft. to ft.	ala I II I	115	225	1
Diam. Slot size Set from ft. to ft.	Claystone Hard			<u> </u>
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? ☐ Yes No If yes, by whom?				 -
Yield: gal./min. with ft. drawdown after hrs.		<u> </u>		
" " "				
Beiler test 12 gal./min. with St. drawdown after 1/2 hrs.				
Artesian flow g.p.m.				
nperature of water Depth artesian flow encounteredft.	Work started March 2 192 Complete	ed Ma	who Z	5 19 H
	Date well drilling machine moved off of well	M	of 2	5 19 X
(9) CONSTRUCTION:	Drilling Machine Operator's Certification	:	- ,	
Well Scar Maderial used	This well was constructed under my	direct	t super	vision.
Well sealed from land surface toft.	Materials used and information reported best knowledge and belief.	above	are true	e to my
Diameter of well bore to bottom of seal in.		Data /	Marl.	5 19 <i>24</i>
Diameter of well bore below sealin.	[Signed] (Drilling Machine Operator)	Date :	erastety di e.	LI LUNCE
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No.		//	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
Number of sacks of bentonite used in well seal sacks				
Brand name of bentonite	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisc	liction a	nd this	report is
of waterlbs./100 gals.	true to the best of my knowledge and be	1161.		
Was a drive shoe used? Yes No Plugs Size: location ft.	Name (Person, firm or corporation).	· (T	ype or pr	int)
Did any strata contain unusable water? Yes No	1 11000 50////	xd"	12 10	54
Type of water? depth of strata	Address 7/90	5/		-4163)
Method of sealing strata off	[Signed]	14	ny	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
Was well gravel packed? Yes No Size of gravel:	(Water Well Cont	Acres	M	
Gravel placed fromft. toft.	Contractor's License No Date	Tinc	125	f., 19 %
	·	F pf		