WATER WELL REPORT STATE OF OREGON	RECEIVED	\$5/1W-	-1-1
STATE OF OREGON	JUN 7 1982 State Well No.	D 1100	- Q Q Q
		/	
MAR 1574 ) 5/17/8:	WATER RESOURCES DEPT to Permit No.  BALEM, OREGON		
(1) OWNER:	(10) LOCATION OF WELL:		
Name KEN SKAGGS	County Marion Driller's well	il number	
Address 252 NW 4th Street	SE 4 SE 4 Section 6 T. 4S	R. 1W	W.M.
City CANBY State OREGON	Tax Lot # 10 Lot Blk	Subdivision	
(2) TYPE OF WORK (check):	Address at well location:	r	
New Well XX Deepening □ Reconditioning □ Abandon □  If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	·	2 <u> ft.</u>
	Static level 12 ft. below le	land surface. Date	4/24/8
Rotary Air   Driven   Domestic XI Industrial   Municipal   Rotary Mud   Dug   Irrigation   Test Well   Other	Artesian pressure lbs. pe	er square inch. Da	te
Bored   Thermal: Withdrawal  Reinjection	(12) WELL LOG: Diameter of well below	casing	611
(5) CASING INSTALLED: Steel Discrete Di	Depth drilled 128 ft. Depth of	completed well	115 ft.
Threaded ☐ Welded ☐  6" Diam from +1 ft. to 94 ft. Gauge .250  1	Formation: Describe color, texture, grain size and struthickness and nature of each stratum and aquifer pene for each change of formation. Report each change in pand indicate principal water-bearing strata.	etrated, with at les	ast one entry
LINER INSTALLED:		<del></del>	<del></del>
4 "Diam from 70 ft. to 90 ft. Gauge PVC	MATERIAL	From To	SWL
	TOP SOIL	0 2	
(6) PERFORATIONS: Perforated?  Yes  XNo	CLAY BROWN	2 18	
Type of perforator used	- OLAT DEGL	18 20	
Size of perforations in. by in.	CLAY GRAY SAND BLACK	20 72	<u> </u>
perforations from ft. to ft.	SAND_BLACK_FINE	72 92	
perforations from ft. to ft.	clay gray SAND BLACK	92 94	
perforations from ft. to ft.	SAND BLACK GRAVEL TRACE	94   110	12 '
(7) SCREENS: Well screen installed? ⋈ Yes □ No	CLAY GRAY SAND BLACK	110 125	
	SAND_BLACK_FINE	125 128	
Manufacturer's Name			
Diam		<b></b>	
Diam. Slot Size		<del> </del>	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
a pump test made? XYes DNo If yes, by whom? driller		<del> </del>	<del> </del>
d: 15 gal/min. with 5 ft. drawdown after 2 hrs.			<del> </del>
11 " " "			<del> </del>
Air test gal./min. with drill stem at ft. hrs.			
Bailer test gal./min. with ft. drawdown after hrs.			<del>                                     </del>
esian flow g.p.m.			
Aperature of water Depth aresian flow encountered ft.	Work started 4-18 1982 Complete	d 4-24	19 82
(9) CONSTRUCTION: Special standards: Yes □ No □	Date well drilling machine moved off of well	4-25	19 82
Well seal—Material usedCemen†	Drilling Machine Operator's Certification:		1002
Well sealed from land surface to	This well was constructed under my direct su		
Diameter of well bore to bottom of sealin.	and information reported above are the to my be	est knowledge e	nd haliaf
Diameter of well bore below seal	[Signed] XIMWW DMA ON	Date 5/15	19.82
Number of sacks of cement used in well seal 25 sacks	V3	38	/···, 10
How was cement grout placed?	Drilling Machine Operator's License No	<i>2.</i> 8	••••••
	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction	and this report	is true to
Was pump installed? Typ	the best of my knowledge and belief.	ropore	uu u w
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	Name BARNETT DRILLING & PUMPS (Person, firm or corporation)	••••••	
Did any strata contain unusable water? Yes No	Address 1.57.50 SOWROLSTADDRIVE	(Type or	print)
Type of Water? deph of strata			UK
Method of sealing strata off	[Signed] Nay Water Well Contractor	ew)	•••••
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	Contractor's License No. Date	<i>n</i> :▼ /1⊑/	10.00
Gravel placed from ft. to ft.		··+D/······	, 1987
A THEFT CONTRACTOR			

State Well No. 55/1W-6dd