5/w 6 E (1)

STATE ENGINEER, STATE OI	State Permit NoG. 1012
(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level
Name Albert J. Fajen	Was a pump test made? M Yes \(\subseteq \text{No If yes, by whom?} \) Driller
Address Rt. 1 Box 251	Yield: 250 gal./min. with 4 ft. drawdown after 7 hrars.
Hadbunn Huxbertx Oregon	" 175 " no " "
11000000111	" 200 " 2 " "
(2) LOCATION OF WELL:	Bailer test gal./min. with ft. drawdown after hrs.
County Mar 1011 Owner's number, if any—	Artesian flow g.p.m. Date
SW 1/4 NW 1/4 Section 6 T. 5 S.R. 7 W.M.	ED
Bearing and distance from section or subdivision corner	Temperature of water O (Was a chemical analysis made? Yes 1 No
	(12) WELL LOG: Diameter of well inches.
· · · · · · · · · · · · · · · · · · ·	Depth drilled 120 ft. Depth of completed well 120 ft.
	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
	MATERIAL FROM TO
(3) TYPE OF WORK (check):	Top Soil 0 3
New Well Deepening Reconditioning Abandon	Yellow silty clay 3 26
Leabandonment, describe material and procedure in Item 11.	Blue clay (sandy) 26 40
PROPOGER TICE (.LL.). (E) WYDE OF WELL.	Blue Clay 40 82
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Black Sand (Fine) 82 100
Domestic Industrial Municipal Rotary Driven Cable Jetted	Black Sand 100 115
Irrigation Test Well Other Dug Bored	Black Sand & Fine gravel 115 120
(FISH FARM)	
(6) CASING INSTALLED: Threaded Welder Welder	This Well was pumped for 3 days at 82 f
10 "Diam. from Top ft. to 120 ft. Gage 31.20#	atamounts up to 400 G.P.M. but well wou
Tt. Gage ft. Gage	not clean up. Well was continued down to
"Diam. from ft. to ft. Gage	
X.	120 ft. and pumped again but would not clean up. A 4" well was drilled down
(7) PERFORATIONS: Perforated? Tyes Tho	hooden the roll were and old be a tal
Type of perforator used	
SIZE of perforations in. by in.	
perforations fromft. toft.	formation through the 4" well but would
perforations from ft. to ft.	take only a small amount of gravel, the
perforations from ft. to ft.	well was steadely pumped and wound up
perforations from ft, to ft.	producing up to 250 G.P.M. with very
perforations from ft. to ft.	little sand.
(8) SCREENS: Well screen installed Yes No	
(0)	
Manufacturer's Name	
TypeModel No.	
Slot size Set from ft. to ft.	0.00.00
Lain. Slot size Set from ft. to ft.	Work started 9-29-58 19 . Completed 11-1-58 19
(9) CONSTRUCTION:	(13) PUMP:
Was well gravel packed? K Yes \(\square\) No Size of gravel: 3/4	
Gravel placed from115. ft. to120ft.	Manufacturer's Name Jacuzzi Bros.
Was a surface seal provided? Tyes No To what depth?14ft.	Type: LineShaft Turbine HP 5 HP SP
Material used in seal— Puddled clay	Well Driller's Statement:
Did any strata contain unusable water? I les X No	
- SAN GA	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Type of water.	that to the book of my intervieuge and belief.
Method of sealing strata off	NAME Emil O. Beier (Person, firm, or corporation) (Type or print)
(10) WATER LEVELS:	l
Static level 30 ft. below and surface Date 11-1-58	Address 7555 O'Neil Rd. Salem, Cregon
Artesian pressure lbs. pr square inch Date	Driller's well number
	Dimer's Well mulliper
Log Accepted by:	[Signed] Concl Deur
Isigned albert Manda Date 11-18 1958	(Well Driller)
[Signed] albert Japan Date 11-18, 1958 by Ramon alany (USE ADDITIONAL SH	License No89 Date
ty Jamon aldny (USE ADDITIONAL SE	LEETS IF NECESSARY)
- A THE STREET OF THE STREET O	THE ALL AND CONTRACT