The original and first copy of this report are to be WATER WELL	L REPRECEIVED	Cl ~	125	
filed with the STATE OF	OREGON State Well No	2 ٦	136	
STATE ENGINEER, SALEM, OREGON 97319 (Please type	or print) $APR9 = 1976$		/	
within 30 days from the date of well completion.	ove this line))		
(1) OWNER:	(10) LQCATION OF WELL:			
Note the	County Marion Driller's well number			
Name (MAC)	12 00 26			
Address Po, 1254 / 1816 Sellen				W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	on corne	<u> </u>	
	-		7	,
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.			
Rotary Driven Domestic Industrial Municipal	Static level 24 ft. below land surface. Date 3-2-7			
Cable Jetted I Irrigation Test Well Other I	Artesian pressure lbs. per square inch. Date			
				,
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well h	elow cas	ing	6
6 "Diam. from + ft. to 86 ft. Gage (236)	Depth drilled & ft. Depth of completed well & ft.			
ft. Gage	Formation: Describe color, texture, grain size a			naterials:
ft. Gage	and show thickness and nature of each stratus	m and a	quifer pe	netrated,
DANDLIOD WANTONIC	with at least one entry for each change of forma position of Static Water Level and indicate prin	tion. Rep	ort each ter-beari	cnange in ng strata.
PERFORATIONS: Perforated? Yes No.		1		
Type of perforator used	MATERIAL	From	То	SWL
Size of perforations in. by in.	Brown Clay	0	9_	
perforations fromft. toft.		4	1100	
perforations from	Clay & Cabbles	4	45	
perforations from		1	1	
(E) CORPERIO	Snown Clay & Sund	1.5	01	<u> </u>
(7) SCREENS: Well screen installed? ☐ Yes ☐ No		j ,	20	
Manufacturer's Name	Attle Clay	101	17	
Type Model No	1 11 1 1 1 1	79	86	<u> </u>
Diam. Slot size Set from ft. to ft.	Small to Large Thouse	177	86	
Diam Slot size Set from ft. to ft.	- March a	ļ		
(8) WELL TESTS: Drawdown is amount water level is				
towered below state level				
Was a pump test made? ☐ Yes ☐ No If yes, by whom?			 	-
Yield: gal./min. with ft. drawdown after hrs.				
n n n		1		
" " "				
Bailer test 4 gal./min. with O ft. drawdown after / hrs.				
Artesian flow g.p.m.				
perature of water Depth artesian flow encountered	Work started 2-16 1976 Complete	ed 3	- /	19 7
perature of water Depart are sain flow excountered		∌ .	1	197 4
(9) CONSTRUCTION:	Date well drilling machine moved off of well	~	- 0-	107 9
Well seal-Material used	Drilling Machine Operator's Certification			
Well sealed from land surface to	This well was constructed under my Materials used and information reported	direc	t supe	rvision. e to mv
Diameter of well bore to bottom of sealin.	best knowledge and belief.			13
Diameter of well bore below seal in.	[Signed Johnson al Ferrila	Date	J-2	1 1976
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	Z	155	•
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.	7		
Brand name of bentonite	Will Continue to the continue to			
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:			
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was a drive shoe used? ✓ Yes ☐ No Plugs Size: location ft.	PORINGONIO ECIA WELL :			
Did any strata contain unusable water? Yes No	Name (Person, fig10 Darrasich), N. V		Type or p	int)
	Address SALEM, OREGON 9730			
	On - Of The State			
Method of sealing strata off	[Signed] HESige N. M. ohn	ro-		*******
Was well gravel packed? Tyes To Size of gravel:	(Water Well Cont		71	/ تري
Gravel placed from ft. to ft.	Contractor's License No. 23 Date	<u> </u>	ر ر	, 19./