State Well No.

NOTICE TO WATER WELL CONTROL FOR A REPORT
The original and first copy of this report are to be
Of this report are to be
JUN 27 197WATER WELL REPORT
filed with the

STATE OF OREGON
STATE ENGINEER, SALEM, OREGON 97355 ENGINEERse type or print)
within 30 days from the dateSALEM OREGON of write above this line)

State Permit No.

(1) OWNER:	(10) LOÇATION OF WELL:
Name (1/12 4/27 HARUS 1877 CO	County Magairian Driller's well number
Address TAY ONS A WASHINGTON	14 14 Section 4 T. 10, S R. 2, 11 W.M.
9840/	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
Rotary Defiven Domestic Industrial Municipal	
Cable	Static level 6 ft. below land surface. Date 6 Artesian pressure lbs. per square inch. Date
	ins. per square men. Date
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing
	Depth drilled 35° ft. Depth of completed well 35° ft.
"Diam. from	Formation: Describe color, texture, grain size and structure of materials;
	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used TOTECH	MATERIAL From To SWL
Size of perforations in. by in.	Right - Sail B
	11 - CANDU 3 12
· · · · · · · · · · · · · · · · · · ·	CLAS & Roya D.
perforations from ft. to ft	1 (31/24/18/
periorations from	AGNICIA -SAND + 12 28
(7) SCREENS: Well screen installed? Yes VNo	MAGON GIZAVIST
Manufacturer's Name	TO LARASS BOOLDING
Type	1200 SAND +1 3836
Diam Slot size Set from ft. to ft.	ATRAMBL WITH
Diam. Slot size Set from ft. to ft.	Some CLAY
(8) WELL TESTS: Drawdown is amount water level is	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? Thes \(\sum \) No If yes, by whom?	KL-jar
You gal./min. with ft. drawdown after fhrs.	-
ıı ıı ıı	
<u>"</u> " "	
Bailer test gal./min. with ft. drawdown after hrs.	
Arresian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 6-/3 - 1923 Completed 6-/6- 1923
(9) CONSTRUCTION:	Date well drilling machine moved off of well 6-/6 - 19 25
Well seal—Material used	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal	Materials used and information reported above are true to my best knowledge and heliof.
Diameter of well bore below seal	[Signed] BIN Seller Date 1073
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No
Brand name of bentonite	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my/knowledge and belief.
Was a drive shoe used? Yes \(\subseteq No \) Plugs Size: locationft.	I I I I I I I I I I I I I I I I I I I
Did any strata contain unusable water? Yes	Name (Person firm or cerporation) (Type or print)
Type of water? depth of strata	Address 5875 (5/AFF/14/11), 51,
Method of sealing strata off	11.1. 50.70.
. , /	[Signed] (Water Well Contractor)
	Contractor's License No. 3.2 Date 6-19-, 197-
Gravel placed from ft. to ft.	- COMMISCION SINCENSE INC. Part Later Later Later Commission of the Commission of th